

## MT46V8M16P-6T L:D TR

#### MT46V8M16P-6T L:D TR Information



#### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### MT46V8M16P-6T L:D TR Specifications

Manufacturer Part Number MT46V8M16P-6T L: D TR   Manufacturer Micron Technology Inc.   Category Integrated Circuits (ICs)   Memory Memory   Package 66-TSSOP (0.400°, 10.16mm Width)   Series -   Memory Type Volatile   Memory Sorrat DRAM   Memory Size SDRAM - DDR   Memory Interface Parallel   Clock Frequency 1578   Vitic Cycle Time - Word, Page 1578   Access Time 700ps   Volating Type SUrface Mount   Mounting Type Surface Mount   Package / Case 66-TSSOP (0.400°, 10.16mm Width)			
CategoryInterretuning, interretuning, int	Manufacturer Part Number	MT46V8M16P-6T L:D TR	
MemoryPackage66-TSSOP (0.400", 10.16mm Width)Series-Memory TypeVolatileMemory FormatDRAMTechnologySDRAM - DDRMemory Size128Mb (8M x 16)Memory InterfaceParallelClock Frequency167MHzWrite Cycle Time - Word, Page15nsAccess Time700psVoltage - Supply2.3 V ~ 2.7 VOperating Temperature0°C ~ 70°C (TA)Mounting TypeSurface MountPackage / Case66-TSSOP (0.400", 10.16mm Width)Supplier Device Package66-TSOP	Manufacturer	Micron Technology Inc.	
Package66-TSOP (0.400", 10.16mm Width)Series-Memory TypeVolatileMemory FormatDRAMTechnologySDRAM - DDRMemory Size128Mb (8M x 16)Memory InterfaceParallelClock Frequency167MHzWrite Cycle Time - Word, Page15nsAccess Time700psVoltage - Supply2.3 V ~ 2.7 VOperating Temperature0°C ~ 70°C (TA)Mounting TypeSurface MountPackage / Case66-TSSOP (0.400", 10.16mm Width)Supplier Device Package66-TSOP	Category	Integrated Circuits (ICs)	
Series-Memory TypeVolatileMemory FormatDRAMTechnologySDRAM - DDRMemory Size128Mb (8M x 16)Memory InterfaceParallelClock Frequency167MHzWrite Cycle Time - Word, Page15nsAccess Time700psVoltage - Supply2.3 V ~ 2.7 VOperating Temperature0°C ~ 70°C (TA)Mounting TypeSurface MountPackage / Case66-TSSOP (0.400", 10.16mm Width)Supplier Device Package66-TSOP		Memory	
Memory TypeVolatileMemory TypeDRAMMemory FormatDRAM - DDRTechnologySDRAM - DDRMemory Size128Mb (8M x 16)Memory InterfaceParallelClock Frequency167MHzWrite Cycle Time - Word, Page15nsAccess Time700psVoltage - Supply2.3 V ~ 2.7 VOperating Temperature0°C ~ 70°C (TA)Mounting TypeSurface MountPackage / Case66-TSSOP (0.400", 10.16mm Width)Supplier Device Package66-TSOP	Package	66-TSSOP (0.400", 10.16mm Width)	
Memory FormatDRAMTechnologySDRAM - DDRMemory Size128Mb (8M x 16)Memory InterfaceParallelClock Frequency167MHzWrite Cycle Time - Word, Page15nsAccess Time700psVoltage - Supply2.3 V ~ 2.7 VOperating Temperature0°C ~ 70°C (TA)Mounting TypeSurface MountPackage / Case66-TSSOP (0.400", 10.16mm Width)Supplier Device Package66-TSOP	Series	-	
TechnologySDRAM - DDRMemory Size128Mb (8M x 16)Memory InterfaceParallelClock Frequency167MHzWrite Cycle Time - Word, Page15nsAccess Time700psVoltage - Supply2.3 V ~ 2.7 VOperating Temperature0°C ~ 70°C (TA)Mounting TypeSurface MountPackage / Case66-TSSOP (0.400", 10.16mm Width)Supplier Device Package66-TSOP	Memory Type	Volatile	
Memory Size 128Mb (8M x 16)   Memory Interface Parallel   Clock Frequency 167MHz   Write Cycle Time - Word, Page 15ns   Access Time 700ps   Voltage - Supply 2.3 V ~ 2.7 V   Operating Temperature 0°C ~ 70°C (TA)   Mounting Type Surface Mount   Package / Case 66-TSSOP (0.400", 10.16mm Width)	Memory Format	DRAM	
Memory InterfaceParallelClock Frequency167MHzWrite Cycle Time - Word, Page15nsAccess Time700psVoltage - Supply2.3 V ~ 2.7 VOperating Temperature0°C ~ 70°C (TA)Mounting TypeSurface MountPackage / Case66-TSSOP (0.400", 10.16mm Width)Supplier Device Package66-TSOP	Technology	SDRAM - DDR	
Clock Frequency 167MHz   Write Cycle Time - Word, Page 15ns   Access Time 700ps   Voltage - Supply 2.3 V ~ 2.7 V   Operating Temperature 0°C ~ 70°C (TA)   Mounting Type Surface Mount   Package / Case 66-TSSOP (0.400", 10.16mm Width)   Supplier Device Package 66-TSOP	Memory Size	128Mb (8M x 16)	
Write Cycle Time - Word, Page15nsAccess Time700psVoltage - Supply2.3 V ~ 2.7 VOperating Temperature0°C ~ 70°C (TA)Mounting TypeSurface MountPackage / Case66-TSSOP (0.400", 10.16mm Width)Supplier Device Package66-TSOP	Memory Interface	Parallel	
Access Time700psVoltage - Supply2.3 V ~ 2.7 VOperating Temperature0°C ~ 70°C (TA)Mounting TypeSurface MountPackage / Case66-TSSOP (0.400", 10.16mm Width)Supplier Device Package66-TSOP	Clock Frequency	167MHz	
Voltage - Supply2.3 V ~ 2.7 VOperating Temperature0°C ~ 70°C (TA)Mounting TypeSurface MountPackage / Case66-TSSOP (0.400", 10.16mm Width)Supplier Device Package66-TSOP	Write Cycle Time - Word, Page	15ns	
Operating Temperature0°C ~ 70°C (TA)Mounting TypeSurface MountPackage / Case66-TSSOP (0.400", 10.16mm Width)Supplier Device Package66-TSOP	Access Time	700ps	
Mounting TypeSurface MountPackage / Case66-TSSOP (0.400", 10.16mm Width)Supplier Device Package66-TSOP	Voltage - Supply	2.3 V ~ 2.7 V	
Package / Case66-TSSOP (0.400", 10.16mm Width)Supplier Device Package66-TSOP	Operating Temperature	$0^{\circ}C \sim 70^{\circ}C$ (TA)	
Supplier Device Package 66-TSOP	Mounting Type	Surface Mount	
	Package / Case	66-TSSOP (0.400", 10.16mm Width)	
Report errors?	Supplier Device Package	66-TSOP	
hepoit chois.			Report errors?

#### MT46V8M16P-6T L:D TR Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### MT46V8M16P-6T L:D TR Payment Methods



If you have any question about MT46V8M16P-6T L:D TR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com