



MUR140-T Information



For Reference Only

Part Number MUR140-T

Manufacturer Diodes Incorporated

Category Discrete Semiconductor Products

Diodes - Rectifiers - Single

Description DIODE GEN PURP 400V 1A DO41

Package DO-204AL, DO-41, Axial

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MUR140-T Specifications

Manufacturer Part NumberMUR140-TManufacturerDiodes IncorporatedCategoryDiscrete Semiconductor ProductsBackageDO-204AL, DO-41, AxialSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If1.25V @ 1ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)75nsCurrent - Reverse Leakage @ Vr5μA @ 400VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-204AL, DO-41, AxialSupplier Device PackageDO-41Operating Temperature - Junction-65°C ~ 175°C	THE TELL TO I Specifications	
Category Discrete Semiconductor Products Diodes - Rectifiers - Single DO-204AL, DO-41, Axial Series - Diode Type Standard Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 75ns Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Through Hole Package / Case DO-204AL, DO-41, Axial Supplier Device Package DO-41 Operating Temperature - Junction	Manufacturer Part Number	MUR140-T
Diodes - Rectifiers - SinglePackageDO-204AL, DO-41, AxialSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If1.25V @ 1ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)75nsCurrent - Reverse Leakage @ Vr5μA @ 400VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-204AL, DO-41, AxialSupplier Device PackageDO-41Operating Temperature - Junction-65°C ~ 175°C	Manufacturer	Diodes Incorporated
PackageDO-204AL, DO-41, AxialSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If1.25V @ 1ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)75nsCurrent - Reverse Leakage @ Vr5μA @ 400VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-204AL, DO-41, AxialSupplier Device PackageDO-41Operating Temperature - Junction-65°C ~ 175°C	Category	Discrete Semiconductor Products
Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If1.25V @ 1ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)75nsCurrent - Reverse Leakage @ Vr5μA @ 400VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-204AL, DO-41, AxialSupplier Device PackageDO-41Operating Temperature - Junction-65°C ~ 175°C		Diodes - Rectifiers - Single
Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If1.25V @ 1ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)75nsCurrent - Reverse Leakage @ Vr5μA @ 400VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-204AL, DO-41, AxialSupplier Device PackageDO-41Operating Temperature - Junction-65°C ~ 175°C	Package	DO-204AL, DO-41, Axial
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) 1A Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery = < 500ns, > 200mA (Io) Reverse Recovery Time (trr) 75ns Current - Reverse Leakage @ Vr 5μA @ 400V Capacitance @ Vr, F Mounting Type Through Hole Package / Case DO-204AL, DO-41, Axial Supplier Device Package Operating Temperature - Junction 400V 1.25V @ 1A Fast Recovery = < 500ns, > 200mA (Io) 75ns Through Hole - Capacitance @ Vr, F DO-204AL, DO-41, Axial DO-41 Operating Temperature - Junction	Series	-
Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 1.25V @ 1A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 75ns Current - Reverse Leakage @ Vr 5µA @ 400V Capacitance @ Vr, F Mounting Type Through Hole Package / Case DO-204AL, DO-41, Axial Supplier Device Package DO-41 Operating Temperature - Junction 1A 1.25V @ 1A 1	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery = < 500ns, > 200mA (Io) Reverse Recovery Time (trr) 75ns Current - Reverse Leakage @ Vr 5µA @ 400V Capacitance @ Vr, F - Mounting Type Through Hole Package / Case DO-204AL, DO-41, Axial Supplier Device Package DO-41 Operating Temperature - Junction 1.25V @ 1A 1.25V @	Voltage - DC Reverse (Vr) (Max)	400V
Speed Fast Recovery =< 500 ns, > 200 mA (Io) Reverse Recovery Time (trr) 75ns Current - Reverse Leakage @ Vr 5μ A @ 400 V Capacitance @ Vr, F - Mounting Type Through Hole Package / Case DO-204AL, DO-41, Axial Supplier Device Package DO-41 Operating Temperature - Junction -65° C ~ 175° C	Current - Average Rectified (Io)	1A
Reverse Recovery Time (trr) 75ns Current - Reverse Leakage @ Vr 5 μ A @ 400V Capacitance @ Vr, F - Mounting Type Through Hole Package / Case DO-204AL, DO-41, Axial Supplier Device Package DO-41 Operating Temperature - Junction -65°C ~ 175°C	Voltage - Forward (Vf) (Max) @ If	1.25V @ 1A
Current - Reverse Leakage @ Vr $5\mu A$ @ $400V$ Capacitance @ Vr, F - Mounting Type Through Hole Package / Case DO-204AL, DO-41, Axial Supplier Device Package DO-41 - $65^{\circ}C \sim 175^{\circ}C$	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F Mounting Type Through Hole Package / Case DO-204AL, DO-41, Axial Supplier Device Package DO-41 Operating Temperature - Junction -65°C ~ 175°C	Reverse Recovery Time (trr)	75ns
Mounting Type Through Hole Package / Case DO-204AL, DO-41, Axial Supplier Device Package DO-41 Operating Temperature - Junction Through Hole -65°C ~ 175°C	Current - Reverse Leakage @ Vr	5μA @ 400V
Package / Case DO-204AL, DO-41, Axial Supplier Device Package DO-41 Operating Temperature - Junction -65°C ~ 175°C	Capacitance @ Vr, F	-
Supplier Device Package DO-41 Operating Temperature - Junction $-65^{\circ}\text{C} \sim 175^{\circ}\text{C}$	Mounting Type	Through Hole
Operating Temperature - Junction -65°C ~ 175°C	Package / Case	DO-204AL, DO-41, Axial
	Supplier Device Package	DO-41
Report errors?	Operating Temperature - Junction	-65°C ~ 175°C
		Report errors?

MUR140-T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MUR140-T Payment Methods





















MUR140-T Shipping Methods













If you have any question about MUR140-T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com