



MUR405 Information



For Reference Only

Part Number MUR405

Manufacturer ON Semiconductor

Category Discrete Semiconductor Products

Diodes - Rectifiers - Single

Description DIODE GEN PURP 50V 4A DO201AD

Package DO-201AA, DO-27, Axial

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MUR405 Specifications

Manufacturer Part NumberMUR405ManufacturerON SemiconductorCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageDO-201AA, DO-27, AxialSeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Io)4AVoltage - Forward (Vf) (Max) @ If890mV @ 4ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5μ @ 50VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction-65°C ~ 175°C	Treative specifications	
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageDO-201AA, DO-27, AxialSeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Io)4AVoltage - Forward (Vf) (Max) @ If890mV @ 4ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5μA @ 50VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction-65°C ~ 175°C	Manufacturer Part Number	MUR405
PackageDiodes - Rectifiers - SingleSeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Io)4AVoltage - Forward (Vf) (Max) @ If890mV @ 4ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5μA @ 50VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction-65°C ~ 175°C	Manufacturer	ON Semiconductor
PackageDO-201AA, DO-27, AxialSeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Io)4AVoltage - Forward (Vf) (Max) @ If890mV @ 4ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5μA @ 50VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction-65°C ~ 175°C	Category	Discrete Semiconductor Products
SeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Io)4AVoltage - Forward (Vf) (Max) @ If890mV @ 4ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5μA @ 50VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction-65°C ~ 175°C		Diodes - Rectifiers - Single
Diode TypeStandardVoltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Io)4AVoltage - Forward (Vf) (Max) @ If890mV @ 4ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5μA @ 50VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction-65°C ~ 175°C	Package	DO-201AA, DO-27, Axial
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 890mV @ 4A Speed Fast Recovery = < 500ns, > 200mA (Io) Reverse Recovery Time (trr) 35ns Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package Operating Temperature - Junction 50V 4A 890mV @ 4A Fast Recovery = < 500ns, > 200mA (Io) 35ns Current - Reverse Leakage @ Vr 5μA @ 50V - Through Hole Package / Case DO-201AA, DO-27, Axial	Series	SWITCHMODE?
Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 890mV @ 4A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 35ns Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package Operating Temperature - Junction 4A 890mV @ 4A 890mV @ 4A Fast Recovery =< 500ns, > 200mA (Io) 35ns Through Hole DO-201AD Operating Temperature - Junction 4A 890mV @ 4A 890mV @ 4A 890mV @ 4A 890mV @ 4A Fast Recovery =< 500ns, > 200mA (Io) 35ns Current - Reverse Leakage DV 5µA @ 50V - Avial DO-201AD Operating Temperature - Junction	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If890mV @ 4ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5μA @ 50VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction-65°C ~ 175°C	Voltage - DC Reverse (Vr) (Max)	50V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5μA @ 50VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction-65°C ~ 175°C	Current - Average Rectified (Io)	4A
Reverse Recovery Time (trr) 35ns Current - Reverse Leakage @ Vr 5 μ A @ 50V Capacitance @ Vr, F - Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package DO-201AD Operating Temperature - Junction -65°C ~ 175°C	Voltage - Forward (Vf) (Max) @ If	890mV @ 4A
Current - Reverse Leakage @ Vr $5\mu A$ @ $50V$ Capacitance @ Vr, F - Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package DO-201AD $-65^{\circ}\text{C} \sim 175^{\circ}\text{C}$	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package DO-201AD Operating Temperature - Junction -65°C ~ 175°C	Reverse Recovery Time (trr)	35ns
Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package DO-201AD Operating Temperature - Junction Through Hole DO-201AA, DO-27, Axial -65°C ~ 175°C	Current - Reverse Leakage @ Vr	5μΑ @ 50V
Package / Case DO-201AA, DO-27, Axial Supplier Device Package DO-201AD Operating Temperature - Junction -65°C ~ 175°C	Capacitance @ Vr, F	-
Supplier Device Package DO-201AD Operating Temperature - Junction -65°C ~ 175°C	Mounting Type	Through Hole
Operating Temperature - Junction -65°C ~ 175°C	Package / Case	DO-201AA, DO-27, Axial
	Supplier Device Package	DO-201AD
Report errors?	Operating Temperature - Junction	-65°C ~ 175°C
		Report errors?

MUR405 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MUR405 Payment Methods





















MUR405 Shipping Methods













If you have any question about MUR405, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com