

MUR415RL

MUR415RL Information

		Part Number Manufacturer Category	MUR415RL ON Semiconductor Discrete Semiconductor Products	
	www.treisener.com	Description Package	Diodes - Rectifiers - Single DIODE GEN PURP 150V 4A DO201AD DO-201AD, Axial For the pricing/inventory/lead time, please contact	
	For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MUR415RL Specifications

Manufacturer Part NumberMUR415RLManufacturerON SemiconductorCategoryDiscrete Semiconductor ProductsDiddes - Rectifiers - SingleDiddes - Rectifiers - SinglePackageDO-201AD, AxialSeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)150VCurrent - Average Rectified (Io)4AVoltage - Forward (Vf) (Max) @ If890mV @ 4ASpeedFast Recovery = < 500ms, > 200mA (Io)Reverse Recovery Time (trr)5jnsCurrent - Reverse Leakage @ Vr-Quating Type-Package / CaseDO-201AD, AxialSupplier Device PackageDO-201AD, AxialSupplier Device PackageDO-201AD, AxialOperating Temperature - Junction-Munuture Temperature - Supplier Device PackageDO-201AD, AxialSupplier Device PackageDO-201AD, AxialSupplier Device PackageDO-201ADSupplier Device PackageDO-201AD <td< th=""><th></th><th></th></td<>		
CategoryDiscrete Semiconductor Products Diodes - Rectifiers - SinglePackageDo-201AD, AxialSeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)150VCurrent - Average Rectified (Io)4AVoltage - Forward (Vf) (Max) @ If890mV @ 4ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)5nsCurrent - Reverse Leakage @ Vr5µA @ 150VCurrent - Reverse Leakage @ Vr5µA @ 150VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction65°C ~ 175°C	Manufacturer Part Number	MUR415RL
Index PackageDiodes - Rectifiers - SinglePackageDO-201AD, AxialSeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)150VCurrent - Average Rectified (Io)4AVoltage - Forward (Vf) (Max) @ If890mV @ 4ASpeedFast Recovery = < 500ms, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5µA @ 150VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction65° ~ 175°C	Manufacturer	ON Semiconductor
PackageDO-201AD, AxialSeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)150VCurrent - Average Rectified (Io)4AVoltage - Forward (Vf) (Max) @ If890mV @ 4ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5µA @ 150VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction65°C ~ 175°C	Category	Discrete Semiconductor Products
SeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)150VCurrent - Average Rectified (Io)4AVoltage - Forward (Vf) (Max) @ If890mV @ 4ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5µA @ 150VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction-65°C ~ 175°C		Diodes - Rectifiers - Single
Diode TypeStandardVoltage - DC Reverse (Vr) (Max)150VCurrent - Average Rectified (Jo)4AVoltage - Forward (Vf) (Max) @ If890mV @ 4ASpeedFast Recovery =< 500ns, > 200mA (Jo)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5µA @ 150VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction-65°C ~ 175°C	Package	DO-201AD, Axial
Voltage - DC Reverse (Vr) (Max)150VCurrent - Average Rectified (Io)4AVoltage - Forward (Vf) (Max) @ If890mV @ 4ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5 μ A @ 150VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction-65°C ~ 175°C	Series	SWITCHMODE?
Current - Average Rectified (Io)4AVoltage - Forward (Vf) (Max) @ If890mV @ 4ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5µA @ 150VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction-65°C ~ 175°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If $890mV @ 4A$ SpeedFast Recovery =< $500ns$, > $200mA$ (Io)Reverse Recovery Time (trr) $35ns$ Current - Reverse Leakage @ Vr $5\muA @ 150V$ Capacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction -65° C ~ 175° C	Voltage - DC Reverse (Vr) (Max)	150V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5μA @ 150VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction-65°C ~ 175°C	Current - Average Rectified (Io)	4A
Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr5µA @ 150VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction-65°C ~ 175°C	Voltage - Forward (Vf) (Max) @ If	890mV @ 4A
Current - Reverse Leakage @ Vr5μA @ 150VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction-65°C ~ 175°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction-65°C ~ 175°C	Reverse Recovery Time (trr)	35ns
Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction-65°C ~ 175°C	Current - Reverse Leakage @ Vr	5μA @ 150V
Package / CaseDO-201AD, AxialSupplier Device PackageDO-201ADOperating Temperature - Junction-65°C ~ 175°C	Capacitance @ Vr, F	-
Supplier Device PackageDO-201ADOperating Temperature - Junction-65°C ~ 175°C	Mounting Type	Through Hole
Operating Temperature - Junction $-65^{\circ}C \sim 175^{\circ}C$	Package / Case	DO-201AD, Axial
	Supplier Device Package	DO-201AD
Report errors	Operating Temperature - Junction	-65°C ~ 175°C
		Report errors?

MUR415RL Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

MUR415RL Payment Methods

MUR415RL Shipping Methods



If you have any question about MUR415RL, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com