

# MUR480ERL

### **MUR480ERL** Information

www.ttelsener.com	Part Number Manufacturer Category Description Package	MUR480ERL ON Semiconductor Discrete Semiconductor Products Diodes - Rectifiers - Single DIODE GEN PURP 800V 4A AXIAL DO-201AD, Axial For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **MUR480ERL Specifications**

ManufacturerON SemiconductorCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageDO-201AD, AxialSeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io)4AVoltage - Forward (Vf) (Max) @ If1.85V @ 4ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)100nsCurrent - Reverse Leakage @ Vr25µA @ 800VCapacitance @ Vr, F-Mouning TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageAxialOperating Temperature - Junction-5°C ~ 175°C		
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageDO-201AD, AxialSeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io)4AVoltage - Forward (Vf) (Max) @ If1.85V @ 4ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)100nsCurrent - Reverse Leakage @ Vr25µA @ 800VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageAxialOperating Temperature - Junction-65°C ~ 175°C	Manufacturer Part Number	MUR480ERL
Diodes - Rectifiers - SinglePackageDO-201AD, AxialSeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io)4AVoltage - Forward (Vf) (Max) @ If1.85V @ 4ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)100nsCurrent - Reverse Leakage @ Vr25µA @ 800VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageAxialOperating Temperature - Junction-65°C ~ 175°C	Manufacturer	ON Semiconductor
PackageDO-201AD, AxialSeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io)4AVoltage - Forward (Vf) (Max) @ If1.85V @ 4ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)100nsCurrent - Reverse Leakage @ Vr25µA @ 800VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageAxialOperating Temperature - Junction-65°C ~ 175°C	Category	Discrete Semiconductor Products
SeriesSWITCHMODE?SeriesStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max) $800V$ Current - Average Rectified (Io) $4A$ Voltage - Forward (Vf) (Max) @ If $1.85V @ 4A$ SpeedFast Recovery =< $500ns, > 200mA$ (Io)Reverse Recovery Time (trr) $100ns$ Current - Reverse Leakage @ Vr $25\muA @ 800V$ Current - Reverse Leakage @ Vr $7hrough Hole$ Package / CaseDO-201AD, AxialSupplier Device PackageAxialOperating Temperature - Junction $65°C ~ 175°C$		Diodes - Rectifiers - Single
Diode TypeStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io)4AVoltage - Forward (Vf) (Max) @ If1.85V @ 4ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)100nsCurrent - Reverse Leakage @ Vr25µA @ 800VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageAxialOperating Temperature - Junction-65°C ~ 175°C	Package	DO-201AD, Axial
Voltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io) $4A$ Voltage - Forward (Vf) (Max) @ If $1.85V @ 4A$ SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr) $100ns$ Current - Reverse Leakage @ Vr $25\mu A @ 800V$ Capacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageAxialOperating Temperature - Junction $-65^\circ C ~ 175^\circ C$	Series	SWITCHMODE?
Current - Average Rectified (Io)4ACurrent - Average Rectified (Io)1.85V @ 4AVoltage - Forward (Vf) (Max) @ If1.85V @ 4ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)100nsCurrent - Reverse Leakage @ Vr25µA @ 800VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageAxialOperating Temperature - Junction-65°C ~ 175°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If $1.85V @ 4A$ SpeedFast Recovery =< $500ns$ , > $200mA$ (Io)Reverse Recovery Time (trr) $100ns$ Current - Reverse Leakage @ Vr $25\muA @ 800V$ Capacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageAxialOperating Temperature - Junction $-65^{\circ}C \sim 175^{\circ}C$	Voltage - DC Reverse (Vr) (Max)	800V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)100nsCurrent - Reverse Leakage @ Vr25µA @ 800VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageAxialOperating Temperature - Junction-65°C ~ 175°C	Current - Average Rectified (Io)	4A
Reverse Recovery Time (trr)100nsCurrent - Reverse Leakage @ Vr25µA @ 800VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageAxialOperating Temperature - Junction-65°C ~ 175°C	Voltage - Forward (Vf) (Max) @ If	1.85V @ 4A
Current - Reverse Leakage @ Vr25µA @ 800VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageAxialOperating Temperature - Junction-65°C ~ 175°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageAxialOperating Temperature - Junction-65°C ~ 175°C	Reverse Recovery Time (trr)	100ns
Mounting TypeThrough HolePackage / CaseDO-201AD, AxialSupplier Device PackageAxialOperating Temperature - Junction-65°C ~ 175°C	Current - Reverse Leakage @ Vr	25µA @ 800V
Package / CaseDO-201AD, AxialSupplier Device PackageAxialOperating Temperature - Junction-65°C ~ 175°C	Capacitance @ Vr, F	-
Supplier Device PackageAxialOperating Temperature - Junction-65°C ~ 175°C	Mounting Type	Through Hole
Operating Temperature - Junction $-65^{\circ}\text{C} \sim 175^{\circ}\text{C}$	Package / Case	DO-201AD, Axial
	Supplier Device Package	Axial
Report errors?	Operating Temperature - Junction	-65°C ~ 175°C
		Report errors?

#### **MUR480ERL** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **MUR480ERL** Payment Methods



# **MUR480ERL** Shipping Methods



If you have any question about MUR480ERL, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com