

MURD330T4G

equest a Quote

MURD330T4G Information

	Part Number	MURD330T4G	
www.neisener.com	Manufacturer	ON Semiconductor	
	Category	Discrete Semiconductor Products Diodes - Rectifiers - Single	j
	Description	DIODE GEN PURP 300V 3A DPAK	
	Package	TO-252-3, DPak (2 Leads + Tab), SC-63	
		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MURD330T4G Specifications

ManufacturerON SemiconductorCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-252-3, DPak (2 Leads + Tab), SC-63SeriesSWTTCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)300VCurrent - Average Rectified (Io)3A (DC)Voltage - Forward (Vf) (Max) @ If1.15V @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5 μ A @ 300VCapacitance @ Vr, F-Mouning TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C		
CategoryDiscrete Semiconductor Products Diodes - Rectifiers - SinglePackageTO-252-3, DPak (2 Leads + Tab), SC-63SeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)300VCurrent - Average Rectified (Io)3A (DC)Voltage - Forward (Vf) (Max) @ If1.15V @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5 μ A @ 300VCurrent - Reverse Leakage @ Vr5 μ A @ 300VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Manufacturer Part Number	MURD330T4G
Indext and the sectifiers - SinglePackageTO-252-3, DPak (2 Leads + Tab), SC-63SeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)300VCurrent - Average Rectified (Io)3A (DC)Voltage - Forward (Vf) (Max) @ If1.15V @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5µA @ 300VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Manufacturer	ON Semiconductor
PackageTO-252-3, DPak (2 Leads + Tab), SC-63SeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)300VCurrent - Average Rectified (Io)3A (DC)Voltage - Forward (Vf) (Max) @ If1.15V @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5µA @ 300VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Category	Discrete Semiconductor Products
SeriesSWITCHMODE?SeriesStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max)300VCurrent - Average Rectified (Io) $3A$ (DC)Voltage - Forward (Vf) (Max) @ If $1.15V$ @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr $5\mu A$ @ 300VCurrent - Reverse Leakage @ Vr $5\mu A$ @ 300VCurrent - Reverse Leakage @ VrSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction -55° C~ 175°C		Diodes - Rectifiers - Single
Diode TypeStandardDiode Type300VVoltage - DC Reverse (Vr) (Max)300VCurrent - Average Rectified (Io)3A (DC)Voltage - Forward (Vf) (Max) @ If1.15V @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5µA @ 300VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Package	TO-252-3, DPak (2 Leads + Tab), SC-63
Voltage - DC Reverse (Vr) (Max) $300V$ Current - Average Rectified (Io) $3A$ (DC)Voltage - Forward (Vf) (Max) @ If $1.15V$ @ $3A$ SpeedFast Recovery =< $500ns$, > $200mA$ (Io)Reverse Recovery Time (trr) $50ns$ Current - Reverse Leakage @ Vr $5\muA$ @ $300V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / Case $TO-252-3$, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction -55° C ~ 175° C	Series	SWITCHMODE?
Current - Average Rectified (Io)3A (DC)Voltage - Forward (Vf) (Max) @ If1.15V @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5µA @ 300VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If $1.15V @ 3A$ SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr) $50ns$ Current - Reverse Leakage @ Vr $5\mu A @ 300V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Voltage - DC Reverse (Vr) (Max)	300V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5µA @ 300VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Current - Average Rectified (Io)	3A (DC)
Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5µA @ 300VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Voltage - Forward (Vf) (Max) @ If	1.15V @ 3A
Current - Reverse Leakage @ Vr5µA @ 300VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Reverse Recovery Time (trr)	50ns
Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Current - Reverse Leakage @ Vr	5µA @ 300V
Package / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Capacitance @ Vr, F	-
Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Mounting Type	Surface Mount
Operating Temperature - Junction $-55^{\circ}C \sim 175^{\circ}C$	Package / Case	TO-252-3, DPak (2 Leads + Tab), SC-63
	Supplier Device Package	DPAK-3
Report errors?	Operating Temperature - Junction	-55°C ~ 175°C
		Report errors?

MURD330T4G Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MURD330T4G Payment Methods



MURD330T4G Shipping Methods



If you have any question about MURD330T4G, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com