

# MURD530T4G

## **MURD530T4G Information**

Www.nosener.com	Part Number Manufacturer Category Description Package	MURD530T4G ON Semiconductor Discrete Semiconductor Products Diodes - Rectifiers - Single DIODE GEN PURP 300V 5A DPAK TO-252-3, DPak (2 Leads + Tab), SC-63 For the pricing/inventory/lead time, please contact	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **MURD530T4G Specifications**

ManufacturerON SemiconductorCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-252-3, DPak (2 Leads + Tab), SC-63SeriesSWTTCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)300VCurrent - Average Rectified (Io)SAVoltage - Forward (Vf) (Max) @ If1.05V @ 5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5µA @ 300VCapacitance @ Vr, F-Mouning TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C		
CategoryDiscrete Semiconductor Products Diodes - Rectifiers - SinglePackageTO-252-3, DPak (2 Leads + Tab), SC-63SeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)300VCurrent - Average Rectified (Io)SAVoltage - Forward (Vf) (Max) @ If1.05V @ 5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5µA @ 300VCurrent - Reverse Leakage @ Vr5µA @ 300VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Manufacturer Part Number	MURD530T4G
Diodes - Rectifiers - SinglePackageTO-252-3, DPak (2 Leads + Tab), SC-63SeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)300VCurrent - Average Rectified (Io)5AVoltage - Forward (Vf) (Max) @ If1.05V @ 5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5 $\mu$ A @ 300VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Manufacturer	ON Semiconductor
PackageTO-252-3, DPak (2 Leads + Tab), SC-63SeriesSWITCHMODE?Diode TypeStandardVoltage - DC Reverse (Vr) (Max) $300V$ Current - Average Rectified (Io) $5A$ Voltage - Forward (Vf) (Max) @ If $1.05V @ 5A$ SpeedFast Recovery =< $500ns, > 200mA$ (Io)Reverse Recovery Time (trr) $50ns$ Current - Reverse Leakage @ Vr $5\muA @ 300V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction $-55°C ~ 175°C$	Category	Discrete Semiconductor Products
SeriesSWITCHMODE?StandardStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max)300VCurrent - Average Rectified (Io) $5A$ Voltage - Forward (Vf) (Max) @ If1.05V @ 5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr $5\mu A$ @ 300VCurrent - Reverse Leakage @ Vr $5\mu A$ @ 300VCurrent - Reverse Leakage @ VrSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction $-55^{\circ}$ C~ 175°C		Diodes - Rectifiers - Single
Diode TypeStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max) $300V$ Current - Average Rectified (Io) $5A$ Voltage - Forward (Vf) (Max) @ If $1.05V @ 5A$ SpeedFast Recovery =< $500ns, > 200mA$ (Io)Reverse Recovery Time (trr) $50ns$ Current - Reverse Leakage @ Vr $5\muA @ 300V$ Capacitance @ Vr, F $-$ Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction $-55^{\circ}C \sim 175^{\circ}C$	Package	TO-252-3, DPak (2 Leads + Tab), SC-63
Voltage - DC Reverse (Vr) (Max) $300V$ Current - Average Rectified (Io) $5A$ Voltage - Forward (Vf) (Max) @ If $1.05V @ 5A$ SpeedFast Recovery =< $500ns$ , > $200mA$ (Io)Reverse Recovery Time (trr) $50ns$ Current - Reverse Leakage @ Vr $5\mu A @ 300V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / Case $TO-252-3$ , DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction $-55^\circ$ C ~ $175^\circ$ C	Series	SWITCHMODE?
Current - Average Rectified (Io)5AVoltage - Forward (Vf) (Max) @ If1.05V @ 5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5µA @ 300VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If $1.05V @ 5A$ SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr) $50ns$ Current - Reverse Leakage @ Vr $5\mu A @ 300V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Voltage - DC Reverse (Vr) (Max)	300V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5µA @ 300VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Current - Average Rectified (Io)	5A
Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5µA @ 300VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Voltage - Forward (Vf) (Max) @ If	1.05V @ 5A
Current - Reverse Leakage @ Vr5μA @ 300VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Reverse Recovery Time (trr)	50ns
Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Current - Reverse Leakage @ Vr	5µA @ 300V
Package / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Capacitance @ Vr, F	-
Supplier Device PackageDPAK-3Operating Temperature - Junction-55°C ~ 175°C	Mounting Type	Surface Mount
Operating Temperature - Junction -55°C ~ 175°C	Package / Case	TO-252-3, DPak (2 Leads + Tab), SC-63
	Supplier Device Package	DPAK-3
Report errors?	Operating Temperature - Junction	-55°C ~ 175°C
		Report errors?

### **MURD530T4G Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## **MURD530T4G Payment Methods**



## MURD530T4G Shipping Methods



If you have any question about MURD530T4G, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com