



MV036T072M017A Information

Heisener.com

Part Number MV036T072M017A

Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description DC DC CONVERTER MIL-COTS

Package Module

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MV036T072M017A Specifications

Manufacturer Vicor Corporation Category Power Supplies - Board Mount DC DC Converters Package Module Series MV036A Type Voltage Transformation Module Number of Outputs 1 Voltage - Input (Min) 26V Voltage - Input (Max) 50V Voltage - Output 1 7.2V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17A Power (Watts) 150W Voltage - Isolation 2.25kV (2250V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 125°C Efficiency 95.9% Mounting Type Through Hole Package / Case Module Size / Dimension 1.28" L x 0.87" W x 0.26" H (32.5mm x 22.0mm x 6.7mm)	Manufacturer Part Number	MV036T072M017A
DC DC Converters	Manufacturer	Vicor Corporation
Package Module Series MV036A Type Voltage Transformation Module Number of Outputs 1 Voltage - Input (Min) 26V Voltage - Input (Max) 50V Voltage - Output 1 7.2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17A Power (Watts) 150W Voltage - Isolation 2.25kV (2250V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 125°C Efficiency 95.9% Mounting Type Through Hole Package / Case Module	Category	Power Supplies - Board Mount
Series MV036A Type Voltage Transformation Module Number of Outputs 1 Voltage - Input (Min) 26V Voltage - Input (Max) 50V Voltage - Output 1 7.2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17A Power (Watts) 150W Voltage - Isolation 2.25kV (2250V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 125°C Efficiency 95.9% Mounting Type Through Hole Package / Case Module		DC DC Converters
TypeVoltage Transformation ModuleNumber of Outputs1Voltage - Input (Min)26VVoltage - Input (Max)50VVoltage - Output 17.2VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)17APower (Watts)150WVoltage - Isolation2.25kV (2250V)ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature-55°C ~ 125°CEfficiency95.9%Mounting TypeThrough HolePackage / CaseModule	Package	Module
Number of Outputs 1 Voltage - Input (Min) 26V Voltage - Input (Max) 50V Voltage - Output 1 7.2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17A Power (Watts) 150W Voltage - Isolation 2.25kV (2250V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 125°C Efficiency 95.9% Mounting Type Through Hole Package / Case Module	Series	MV036A
Voltage - Input (Min) 26V Voltage - Output 1 7.2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17A Power (Watts) 150W Voltage - Isolation 2.25kV (2250V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 125°C Efficiency 95.9% Mounting Type Through Hole Package / Case Module	Туре	Voltage Transformation Module
Voltage - Input (Max) 50V Voltage - Output 1 7.2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17A Power (Watts) 150W Voltage - Isolation 2.25kV (2250V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 125°C Efficiency 95.9% Mounting Type Through Hole Package / Case Module	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications Features OCP, OTP, OVP, SCP Operating Temperature Efficiency Mounting Type Mounting Type Package / Case Module	Voltage - Input (Min)	26V
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17A Power (Watts) 150W Voltage - Isolation 2.25kV (2250V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 125°C Efficiency 95.9% Mounting Type Through Hole Package / Case Module	Voltage - Input (Max)	50V
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature Efficiency Mounting Type Package / Case Module	Voltage - Output 1	7.2V
Voltage - Output 4 - Current - Output (Max) 17A Power (Watts) 150W Voltage - Isolation 2.25kV (2250V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 125°C Efficiency 95.9% Mounting Type Through Hole Package / Case Module	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 150W Voltage - Isolation 2.25kV (2250V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 125°C Efficiency 95.9% Mounting Type Through Hole Package / Case Module	Voltage - Output 3	-
Power (Watts) Voltage - Isolation 2.25kV (2250V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 125°C Efficiency 95.9% Mounting Type Through Hole Package / Case Module	Voltage - Output 4	-
Voltage - Isolation 2.25kV (2250V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 125°C Efficiency 95.9% Mounting Type Through Hole Package / Case Module	Current - Output (Max)	17A
Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 125°C Efficiency 95.9% Mounting Type Through Hole Package / Case Module	Power (Watts)	150W
Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 125°C Efficiency 95.9% Mounting Type Through Hole Package / Case Module	Voltage - Isolation	2.25kV (2250V)
Operating Temperature -55°C ~ 125°C Efficiency 95.9% Mounting Type Through Hole Package / Case Module	Applications	ITE (Commercial)
Efficiency 95.9% Mounting Type Through Hole Package / Case Module	Features	OCP, OTP, OVP, SCP
Mounting Type Through Hole Package / Case Module	Operating Temperature	-55°C ~ 125°C
Package / Case Module	Efficiency	95.9%
	Mounting Type	Through Hole
Size / Dimension 1.28" L x 0.87" W x 0.26" H (32.5mm x 22.0mm x 6.7mm)	Package / Case	Module
	Size / Dimension	1.28" L x 0.87" W x 0.26" H (32.5mm x 22.0mm x 6.7mm)

Supplier Device Package	-
Control Features	-
	Report errors?

MV036T072M017A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MV036T072M017A Payment Methods





















MV036T072M017A Shipping Methods













If you have any question about MV036T072M017A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com