



MV6700AGR Information

Heisener.com

Part Number MV6700AGR

Manufacturer Everlight Electronics Co Ltd

Category Optoelectronics

LED Indication - Discrete

Description LED RED DIFFUSED 2SMD GW

Package 2-SMD, Gull Wing

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MV6700AGR Specifications

Manufacturer Part Number MV6700AGR Manufacturer Everlight Electronics Co Ltd Category Optoelectronics LED Indication - Discrete Package 2-SMD, Gull Wing Series - Color Red Configuration - Lens Color Red Lens Transparency Diffused Millicandela Rating 3mcd Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 1.8V Current - Test 10mA Viewing Angle 50° Mounting Type Surface Mount Wavelength - Dominant - Wavelength - Peak 635mm Features - Supplier Device Package T-3/4 Size / Dimension 2.20mm L x 2.10mm W Height (Max) 1.92mm		
Category Optoelectronics LED Indication - Discrete Package 2-SMD, Gull Wing Series - Color Red Configuration - Lens Color Red Lens Transparency Diffused Millicandela Rating 3mcd Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 1.8V Current - Test 10mA Viewing Angle 50° Mounting Type Surface Mount Wavelength - Dominant - Wavelength - Peak 635nm Features - Package / Case 2-SMD, Gull Wing Supplier Device Package T-3/4 Size / Dimension 2.20mm L x 2.10mm W Height (Max) 2.92mm	Manufacturer Part Number	MV6700AGR
Package 2-SMD, Gull Wing Series - Color Red Configuration - Lens Color Red Lens Transparency Diffused Millicandela Rating 3mcd Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 1.8V Current - Test 10mA Viewing Angle 50° Mounting Type Surface Mount Wavelength - Dominant - Wavelength - Peak 635nm Features - Package / Case 2-SMD, Gull Wing Supplier Device Package T-3/4 Size / Dimension 2.20mm L x 2.10mm W Height (Max) 2.92mm	Manufacturer	Everlight Electronics Co Ltd
Package 2-SMD, Gull Wing Series - Color Red Configuration - Lens Color Red Lens Transparency Diffused Millicandela Rating 3mcd Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 1.8V Current - Test 10mA Viewing Angle 50° Mounting Type Surface Mount Wavelength - Dominant - Wavelength - Peak 635nm Features - Package / Case 2-SMD, Gull Wing Supplier Device Package T-3/4 Size / Dimension 2.20mm L x 2.10mm W Height (Max) 2.92mm	Category	Optoelectronics
Series - Color Red Configuration - Lens Color Red Lens Transparency Diffused Millicandela Rating 3mcd Lens Style/Size Round with Domed Top, 1,90mm Voltage - Forward (Vf) (Typ) 1.8V Current - Test 10mA Viewing Angle 50° Mounting Type Surface Mount Wavelength - Dominant - Wavelength - Peak 635nm Features - Package / Case 2-SMD, Gull Wing Supplier Device Package T-3/4 Size / Dimension 2.20mm L x 2.10mm W Height (Max) 2.92mm		LED Indication - Discrete
Color Red Configuration - Lens Color Red Lens Transparency Diffused Millicandela Rating 3mcd Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 1.8V Current - Test 10mA Viewing Angle 50° Mounting Type Surface Mount Wavelength - Dominant - Wavelength - Peak 635nm Features - Package / Case 2-SMD, Gull Wing Supplier Device Package T-3/4 Size / Dimension 2.20mm L x 2.10mm W Height (Max) 2.92mm	Package	2-SMD, Gull Wing
Configuration-Lens ColorRedLens TransparencyDiffusedMillicandela Rating3mcdLens Style/SizeRound with Domed Top, 1.90mmVoltage - Forward (Vf) (Typ)1.8VCurrent - Test10mAViewing Angle50°Mounting TypeSurface MountWavelength - Dominant-Wavelength - Peak635nmFeatures-Package / Case2-SMD, Gull WingSupplier Device PackageT-3/4Size / Dimension2.20mm L x 2.10mm WHeight (Max)2.92mm	Series	-
Lens ColorRedLens TransparencyDiffusedMillicandela Rating3mcdLens Style/SizeRound with Domed Top, 1.90mmVoltage - Forward (Vf) (Typ)1.8VCurrent - Test10mAViewing Angle50°Mounting TypeSurface MountWavelength - Dominant-Features-Package / Case2-SMD, Gull WingSupplier Device PackageT-3/4Size / Dimension2.20mm L x 2.10mm WHeight (Max)2.92mm	Color	Red
Lens TransparencyDiffusedMillicandela Rating3mcdLens Style/SizeRound with Domed Top, 1.90mmVoltage - Forward (Vf) (Typ)1.8VCurrent - Test10mAViewing Angle50°Mounting TypeSurface MountWavelength - Dominant-Wavelength - Peak635nmFeatures-Package / Case2-SMD, Gull WingSupplier Device PackageT-3/4Size / Dimension2.20mm L x 2.10mm WHeight (Max)2.92mm	Configuration	-
Millicandela Rating Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 1.8V Current - Test 10mA Viewing Angle Surface Mount Wavelength - Dominant - Wavelength - Peak 635nm Features - Package / Case 2-SMD, Gull Wing Supplier Device Package T-3/4 Size / Dimension Lens Style/Size Round with Domed Top, 1.90mm 1.8V Round with Domed Top, 1.90mm 1.8V 1.8V 1.8V 50° Surface Mount	Lens Color	Red
Lens Style/SizeRound with Domed Top, 1.90mmVoltage - Forward (Vf) (Typ)1.8VCurrent - Test10mAViewing Angle50°Mounting TypeSurface MountWavelength - Dominant-Wavelength - Peak635nmFeatures-Package / Case2-SMD, Gull WingSupplier Device PackageT-3/4Size / Dimension2.20mm L x 2.10mm WHeight (Max)2.92mm	Lens Transparency	Diffused
Voltage - Forward (Vf) (Typ) Current - Test 10mA Viewing Angle 50° Mounting Type Surface Mount Wavelength - Dominant - Wavelength - Peak 635nm Features - Package / Case 2-SMD, Gull Wing Supplier Device Package T-3/4 Size / Dimension Height (Max) 1.8V 10mA 50° Surface Mount - C Surface Mount - C Surface Mount - C 2-SMD 635nm 2-SMD 7-3/4 52.20mm L x 2.10mm W 2.292mm	Millicandela Rating	3mcd
Current - Test 10mA Viewing Angle 50° Mounting Type Surface Mount Wavelength - Dominant - Wavelength - Peak 635nm Features - Package / Case 2-SMD, Gull Wing Supplier Device Package T-3/4 Size / Dimension 2.20mm L x 2.10mm W Height (Max) 2.92mm	Lens Style/Size	Round with Domed Top, 1.90mm
Viewing Angle50°Mounting TypeSurface MountWavelength - Dominant-Wavelength - Peak635nmFeatures-Package / Case2-SMD, Gull WingSupplier Device PackageT-3/4Size / Dimension2.20mm L x 2.10mm WHeight (Max)2.92mm	Voltage - Forward (Vf) (Typ)	1.8V
Mounting Type Surface Mount Wavelength - Dominant - Wavelength - Peak 635nm Features - Package / Case 2-SMD, Gull Wing Supplier Device Package T-3/4 Size / Dimension 2.20mm L x 2.10mm W Height (Max) 2.92mm	Current - Test	10mA
Wavelength - Dominant Wavelength - Peak 635nm Features - Package / Case 2-SMD, Gull Wing Supplier Device Package T-3/4 Size / Dimension 2.20mm L x 2.10mm W Height (Max) 2.92mm	Viewing Angle	50°
Wavelength - Peak 635nm Features - Package / Case 2-SMD, Gull Wing Supplier Device Package T-3/4 Size / Dimension 2.20mm L x 2.10mm W Height (Max) 2.92mm	Mounting Type	Surface Mount
Features - Package / Case 2-SMD, Gull Wing Supplier Device Package T-3/4 Size / Dimension 2.20mm L x 2.10mm W Height (Max) 2.92mm	Wavelength - Dominant	-
Package / Case 2-SMD, Gull Wing Supplier Device Package T-3/4 Size / Dimension 2.20mm L x 2.10mm W Height (Max) 2.92mm	Wavelength - Peak	635nm
Supplier Device Package T-3/4 Size / Dimension 2.20mm L x 2.10mm W Height (Max) 2.92mm	Features	-
Size / Dimension 2.20mm L x 2.10mm W Height (Max) 2.92mm	Package / Case	2-SMD, Gull Wing
Height (Max) 2.92mm	Supplier Device Package	T-3/4
	Size / Dimension	2.20mm L x 2.10mm W
Report errors?	Height (Max)	2.92mm
		Report errors?

MV6700AGR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MV6700AGR Payment Methods



















MV6700AGR Shipping Methods













If you have any question about MV6700AGR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com