

Heisener.com

MVA50VC22RMF55TP

MVA50VC22RMF55TP Information

Part Number MVA50VC22RMF55TP

Manufacturer United Chemi-Con

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 22UF 20% 50V SMD

Package Radial, Can - SMD

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MVA50VC22RMF55TP Specifications

Manufacturer Part Number MVA50VC22RMF55TP Manufacturer United Chemi-Con Category Capacitors Package Radial, Can - SMD Series MVA Capacitance 22µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 9.041 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 47mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.205" (5.20mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm) Mounting Type Surface Mount	*	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - SMD Series MVA Capacitance 22μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 9.041 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 47mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.205" (5.20mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Manufacturer Part Number	MVA50VC22RMF55TP
Aluminum Electrolytic Capacitors Package Radial, Can - SMD Series MVA Capacitance 22µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 9.041 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 47mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.205" (5.20mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Manufacturer	United Chemi-Con
Package Radial, Can - SMD Series MVA Capacitance 22μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 9.041 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 47mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.205" (5.20mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Category	Capacitors
Series MVA Capacitance 22μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 9.041 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 47mA @ 120Hz Ripple Current - High Frequency - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.205" (5.20mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)		Aluminum Electrolytic Capacitors
Capacitance 22μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 9.041 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 47mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.205" (5.20mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Package	Radial, Can - SMD
Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 9.041 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 47mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.205" (5.20mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Series	MVA
Voltage - Rated ESR (Equivalent Series Resistance) 9.041 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 47mA @ 120Hz Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size 50V 9.041 Ohm @ 120Hz 2000 Hrs @ 85°C -40°C ~ 85°C Folarization -40°C ~ 85°C -40°C ~	Capacitance	22μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size 9.041 Ohm @ 120Hz 2000 Hrs @ 85°C -40°C ~ 85°C Polar -40°C ~ 85°C -40°C ~ 80°C ~ 80°C -40°C ~ 80°C	Tolerance	±20%
Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 47mA @ 120Hz Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size 2000 Hrs @ 85°C -40°C ~ 85°C Polar April Current -40°C ~ 85°C Polar -40°C ~ 85°C Polar -40°C ~ 85°C -40°C -40°C ~ 85°C -40°C -40°C -40°C ~ 85°C -40°C -40°C	Voltage - Rated	50V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency AfmA @ 120Hz Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension U.248" Dia (6.30mm) Height - Seated (Max) Surface Mount Land Size -40°C ~ 85°C Polar General Purpose	ESR (Equivalent Series Resistance)	9.041 Ohm @ 120Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 47mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.205" (5.20mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications General Purpose 47mA @ 120Hz Apple Current - Low Frequency Apple Current - High Frequency Impedance Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size General Purpose 47mA @ 120Hz - 0.248" Dia (6.30mm) 0.248" Dia (6.30mm) 0.205" (5.20mm) 0.260" L x 0.260" W (6.60mm x 6.60mm)	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency 47mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.205" (5.20mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Polarization	Polar
Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.205" (5.20mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Applications	General Purpose
Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.205" (5.20mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Ripple Current - Low Frequency	47mA @ 120Hz
Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.205" (5.20mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Ripple Current - High Frequency	-
Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.205" (5.20mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Impedance	-
Height - Seated (Max) 0.205" (5.20mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Lead Spacing	-
Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Size / Dimension	0.248" Dia (6.30mm)
	Height - Seated (Max)	0.205" (5.20mm)
Mounting Type Surface Mount	Surface Mount Land Size	0.260" L x 0.260" W (6.60mm x 6.60mm)
	Mounting Type	Surface Mount
Package / Case Radial, Can - SMD	Package / Case	Radial, Can - SMD
Report errors?		Report errors?

MVA50VC22RMF55TP Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MVA50VC22RMF55TP Payment Methods



















MVA50VC22RMF55TP Shipping Methods













If you have any question about MVA50VC22RMF55TP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com