

Heisener.com

MVH25VC101MH10TP

MVH25VC101MH10TP Information

Part Number MVH25VC101MH10TP

Manufacturer United Chemi-Con

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 100UF 20% 25V SMD

Package Radial, Can - SMD

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MVH25VC101MH10TP Specifications

Manufacturer Part Number MVH25VC101MH10TP Manufacturer United Chemi-Con Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - SMD Series MVH Capacitance 100µF Tolerance ±20% Voltage - Rated 25 V ESR (Equivalent Series Resistance) 1 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polar Applications Ripple Current - Low Frequency - Ripple Current - High Frequency 126mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.394" (10.00mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	•	
Category Capacitors Package Radial, Can - SMD Series MVH Capacitance 100µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 1 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 126mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.394" (10.00mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Manufacturer Part Number	MVH25VC101MH10TP
PackageAluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesMVHCapacitance100μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)1 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency126mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.394" (10.00mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Manufacturer	United Chemi-Con
Package Radial, Can - SMD Series MVH Capacitance 100µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 1 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 126mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.394" (10.00mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Category	Capacitors
Series MVH Capacitance 100μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 1 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 126mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.394" (10.00mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD		Aluminum Electrolytic Capacitors
Capacitance100μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)1 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency126mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.394" (10.00mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Package	Radial, Can - SMD
Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 1 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 126mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.394" (10.00mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Series	MVH
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 126mA @ 100kHz Impedance - Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Capacitance	100μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Applications General Purpose Ripple Current - Low Frequency -Ripple Current - High Frequency 126mA @ 100kHz Impedance -Lead Spacing -Size / Dimension Height - Seated (Max) Surface Mount Land Size O.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Ripole Current - High Frequency 1 2000 Hrs @ 125°C 2000 Hrs @ 1	Tolerance	±20%
Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency Inpedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Polar 2000 Hrs @ 125°C -40°C ~ 125°C General Purpose - 126mA @ 100kHz - 126mA @ 100kHz - 100k	Voltage - Rated	25V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Polar P	ESR (Equivalent Series Resistance)	1 Ohm @ 120Hz
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - Low Frequency Ripple Curr	Lifetime @ Temp.	2000 Hrs @ 125°C
Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 126mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.394" (10.00mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Operating Temperature	-40°C ~ 125°C
Ripple Current - Low Frequency - 126mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.394" (10.00mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size O.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Applications	General Purpose
Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.394" (10.00mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Ripple Current - Low Frequency	-
Lead Spacing - O.315" Dia (8.00mm) Height - Seated (Max) O.394" (10.00mm) Surface Mount Land Size O.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Ripple Current - High Frequency	126mA @ 100kHz
Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.394" (10.00mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Impedance	-
Height - Seated (Max) Surface Mount Land Size 0.394" (10.00mm) 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Lead Spacing	-
Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Size / Dimension	0.315" Dia (8.00mm)
Mounting Type Surface Mount Package / Case Radial, Can - SMD	Height - Seated (Max)	0.394" (10.00mm)
Package / Case Radial, Can - SMD	Surface Mount Land Size	0.327" L x 0.327" W (8.30mm x 8.30mm)
	Mounting Type	Surface Mount
Report errors?	Package / Case	Radial, Can - SMD
1		Report errors?

MVH25VC101MH10TP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MVH25VC101MH10TP Payment Methods

































If you have any question about MVH25VC101MH10TP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com