



#### MW2424-760-NC-WH Information



For Reference Only

Part Number MW2424-760-NC-WH

Manufacturer Inventus Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 24V 24W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## MW2424-760-NC-WH Specifications

Manufacturer Part Number         MW2424-760-NC-WH           Manufacturer         Inventus Power           Category         Power Supplies - External/Internal (Off-Board)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         MW24           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         100 ~ 240 VAC           Voltage - Output         24V           Current - Output (Max)         1A           Power (Watts)         24W           No Load Power Consumption         -           Polarization         Positive Center           Applications         Medical           Efficiency         80%           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Manufacturer Part Number	MW2424-760-NC-WH
AC DC Desktop, Wall Adapters  Package Series MW24  Region Utilized International  Form Desktop (Class I)  Input Type Cord (Sold Separately)  Voltage - Input 100 ~ 240 VAC  Voltage - Output 24V  Current - Output (Max) 1A  Power (Watts) 24W  No Load Power Consumption -  Polarization Positive Center  Applications Medical  Efficiency 80%  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Manufacturer	Inventus Power
Package         -           Series         MW24           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         100 ~ 240 VAC           Voltage - Output         24V           Current - Output (Max)         1A           Power (Watts)         24W           No Load Power Consumption         -           Polarization         Positive Center           Applications         Medical           Efficiency         80%           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesMW24Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output $24V$ Current - Output (Max) $1A$ Power (Watts) $24W$ No Load Power Consumption-PolarizationPositive CenterApplicationsMedicalEfficiency $80\%$ Operating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug, $2.5 \text{ mm I.D. x } 5.5 \text{ mm O.D. x } 9.5 \text{ mm x } 33.0 \text{ mm})$ Size / Dimension $4.25^{\circ}$ L x $2.50^{\circ}$ W x $1.30^{\circ}$ H ( $108.0 \text{ mm x } 64.5 \text{ mm x } 33.0 \text{ mm})$		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output24VCurrent - Output (Max)1APower (Watts)24WNo Load Power Consumption-PolarizationPositive CenterApplicationsMedicalEfficiency80%Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC  Voltage - Output 24V Current - Output (Max) 1A Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications Medical Efficiency 80% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Series	MW24
Input Type Cord (Sold Separately)  Voltage - Input 100 ~ 240 VAC  Voltage - Output 24V  Current - Output (Max) 1A  Power (Watts) 24W  No Load Power Consumption -  Polarization Positive Center  Applications Medical  Efficiency 80%  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Region Utilized	International
Voltage - Input  100 ~ 240 VAC  Voltage - Output  24V  Current - Output (Max)  1A  Power (Watts)  No Load Power Consumption  Polarization  Positive Center  Applications  Medical  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  100 ~ 240 VAC  24V  A  Current - Output (Max)  1A  Power (Watts)	Form	Desktop (Class I)
Voltage - Output  Current - Output (Max)  1A  Power (Watts)  No Load Power Consumption  Polarization  Polarization  Applications  Efficiency  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  24V  24V  Adv  Adv  Adv  Adv  Adv  Adv  Adv  Ad	Input Type	Cord (Sold Separately)
Current - Output (Max)  Power (Watts)  24W  No Load Power Consumption  - Polarization  Positive Center  Applications  Medical  Efficiency  80%  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts)  24W  No Load Power Consumption  Polarization  Positive Center  Applications  Medical  Efficiency  80%  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Voltage - Output	24V
No Load Power Consumption-PolarizationPositive CenterApplicationsMedicalEfficiency $80\%$ Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.5\text{mm}$ I.D. $x$ $5.5\text{mm}$ O.D. $x$ $9.5\text{mm}$ Size / Dimension $4.25$ " L $x$ $2.50$ " W $x$ $1.30$ " H ( $108.0\text{mm}$ $x$ $64.5\text{mm}$ $x$ $33.0\text{mm}$ )	Current - Output (Max)	1A
Polarization Positive Center  Applications Medical  Efficiency 80%  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $4.25^{\circ}\text{L} \times 2.50^{\circ}\text{W} \times 1.30^{\circ}\text{H} (108.0 \text{mm} \times 64.5 \text{mm} \times 33.0 \text{mm})$	Power (Watts)	24W
Applications Medical   Efficiency 80%   Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm   Size / Dimension 4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	No Load Power Consumption	-
Efficiency       80%         Operating Temperature       0°C ~ 40°C         Output Connector       Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm         Size / Dimension       4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.25^{\circ}\text{L} \times 2.50^{\circ}\text{W} \times 1.30^{\circ}\text{H} (108.0\text{mm} \times 64.5\text{mm} \times 33.0\text{mm})$	Applications	Medical
Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Efficiency	80%
Size / Dimension 4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Operating Temperature	$0^{\circ}\text{C} \sim 40^{\circ}\text{C}$
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)
		Report errors

#### MW2424-760-NC-WH Guarantees



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MW2424-760-NC-WH Payment Methods



















# **MW2424-760-NC-WH Shipping Methods**













If you have any question about MW2424-760-NC-WH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com