



#### MW4018-760-NC-BK Information



For Reference Only

Part Number MW4018-760-NC-BK

Manufacturer Inventus Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 18V 40W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### MW4018-760-NC-BK Specifications

Manufacturer Part Number         MW4018-760-NC-BK           Manufacturer         Inventus Power           Category         Power Supplies - External/Internal (Off-Board)           Reckage         -           Series         MW40           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         100 ~ 240 VAC           Voltage - Output         18V           Current - Output (Max)         2.2A           Power (Watts)         40W           No Load Power Consumption         -           Polarization         Positive Center           Applications         Medical           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)    Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         MW40           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         100 ~ 240 VAC           Voltage - Output         18V           Current - Output (Max)         2.2A           Power (Watts)         40W           No Load Power Consumption         -           Polarization         Positive Center           Applications         Medical           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Manufacturer Part Number	MW4018-760-NC-BK
Package-SeriesMW40Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output18VCurrent - Output (Max)2.2APower (Watts)40WNo Load Power Consumption-PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Manufacturer	Inventus Power
Package         -           Series         MW40           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         100 ~ 240 VAC           Voltage - Output         18V           Current - Output (Max)         2.2A           Power (Watts)         40W           No Load Power Consumption         -           Polarization         Positive Center           Applications         Medical           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesMW40Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output $18V$ Current - Output (Max) $2.2A$ Power (Watts) $40W$ No Load Power Consumption-PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug, $2.5 \text{mm I.D. x 5.5 mm O.D. x 9.5 mm}$ Size / Dimension $5.00^{\circ}$ L x $3.00^{\circ}$ W x $1.30^{\circ}$ H ( $127.0 \text{mm x 76.2 mm x 33.0 mm}$ )		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 18V Current - Output (Max) 2.2A Power (Watts) 40W No Load Power Consumption - Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output $18\text{V}$ Current - Output (Max) $2.2\text{A}$ Power (Watts) $40\text{W}$ No Load Power Consumption - Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, $2.5\text{mm} \text{ I.D. x } 5.5\text{mm} \text{ O.D. x } 9.5\text{mm} \times 33.0\text{mm}$ Size / Dimension $5.00^{\circ}\text{L x } 3.00^{\circ}\text{W x } 1.30^{\circ}\text{H } (127.0\text{mm x } 76.2\text{mm x } 33.0\text{mm})$	Series	MW40
Input Type Cord (Sold Separately)  Voltage - Input 100 ~ 240 VAC  Voltage - Output 18V  Current - Output (Max) 2.2A  Power (Watts) 40W  No Load Power Consumption -  Polarization Positive Center  Applications Medical  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Region Utilized	International
Voltage - Input  100 ~ 240 VAC  Voltage - Output  18V  Current - Output (Max)  2.2A  Power (Watts)  No Load Power Consumption  Polarization  Positive Center  Applications  Medical  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  18V  2.2A  40W  No Load Power Consumption  -  Positive Center  Medical  Level V  Operating Temperature  0°C ~ 40°C  Sarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Form	Desktop (Class I)
Voltage - Output  Current - Output (Max)  2.2A  Power (Watts)  No Load Power Consumption  Polarization  Polarization  Applications  Efficiency  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  18V  2.2A  40W  Available  40W  Available  Positive Center  Medical  Level V  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max)  2.2A  Power (Watts)  40W  No Load Power Consumption  - Polarization  Applications  Medical  Efficiency  Level V  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts) $40W$ No Load Power Consumption-PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature $0^{\circ}$ C ~ $40^{\circ}$ COutput ConnectorBarrel Plug, $2.5$ mm I.D. $x 5.5$ mm O.D. $x 9.5$ mmSize / Dimension $5.00$ " L $x 3.00$ " W $x 1.30$ " H ( $127.0$ mm $x 76.2$ mm $x 33.0$ mm)	Voltage - Output	18V
No Load Power Consumption-PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature $0^{\circ}$ C ~ $40^{\circ}$ COutput ConnectorBarrel Plug, $2.5$ mm I.D. $x 5.5$ mm O.D. $x 9.5$ mmSize / Dimension $5.00$ " L $x 3.00$ " W $x 1.30$ " H ( $127.0$ mm $x 76.2$ mm $x 33.0$ mm)	Current - Output (Max)	2.2A
Polarization Positive Center  Applications Medical  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $5.00^{\circ}\text{L} \times 3.00^{\circ}\text{W} \times 1.30^{\circ}\text{H} (127.0\text{mm} \times 76.2\text{mm} \times 33.0\text{mm})$	Power (Watts)	40W
Applications Medical  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $5.00^{\circ}\text{L} \times 3.00^{\circ}\text{W} \times 1.30^{\circ}\text{H} (127.0\text{mm} \times 76.2\text{mm} \times 33.0\text{mm})$	No Load Power Consumption	-
Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $5.00^{\circ}\text{L} \times 3.00^{\circ}\text{W} \times 1.30^{\circ}\text{H} (127.0\text{mm} \times 76.2\text{mm} \times 33.0\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $5.00^{\circ}\text{L x }3.00^{\circ}\text{W x }1.30^{\circ}\text{H }(127.0\text{mm x }76.2\text{mm x }33.0\text{mm})$	Applications	Medical
Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Efficiency	Level V
Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)
		Report errors?

#### MW4018-760-NC-BK Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MW4018-760-NC-BK Payment Methods



















## MW4018-760-NC-BK Shipping Methods













If you have any question about MW4018-760-NC-BK, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com