



MWA080024A-12A Information



For Reference Only

Part Number MWA080024A-12A Manufacturer Inventus Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 24V 80W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MWA080024A-12A Specifications

Manufacturer Part Number MWA080024A-12A Manufacturer Inventus Power Category Power Supplies - External/Internal (Off-Board) Reckage - Series MWA080 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 3.3A Power (Watts) 79W No Load Power Consumption 500mW (Max) Polarization - Applications Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series MWA080 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 3.3A Power (Watts) 79W No Load Power Consumption 500mW (Max) Polarization - Applications Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Manufacturer Part Number	MWA080024A-12A
Package - Series MWA080 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 3.3A Power (Watts) 79W No Load Power Consumption 500mW (Max) Polarization - Applications Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Manufacturer	Inventus Power
Package - Series MWA080 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 3.3A Power (Watts) 79W No Load Power Consumption 500mW (Max) Polarization - Applications Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesMWA080Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input85 ~ 264 VACVoltage - Output24VCurrent - Output (Max)3.3APower (Watts)79WNo Load Power Consumption500mW (Max)Polarization-ApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 60°COutput ConnectorDIN, 8 PinSize / Dimension5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 3.3A Power (Watts) 79W No Load Power Consumption 500mW (Max) Polarization - Applications Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Package	-
FormDesktop (Class I)Input Type $Cord$ (Sold Separately)Voltage - Input $85 \sim 264 \text{ VAC}$ Voltage - Output 24V Current - Output (Max) 3.3A Power (Watts) 79W No Load Power Consumption 500mW (Max)Polarization-ApplicationsMedicalEfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorDIN, 8 PinSize / Dimension $5.19^{\circ}\text{L x 3.07}^{\circ}\text{W x 1.34}^{\circ}\text{H (132.0mm x 78.0mm x 34.0mm)}$	Series	MWA080
Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 3.3A Power (Watts) 79W No Load Power Consumption 500mW (Max) Polarization - Applications Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Region Utilized	International
Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 79W No Load Power Consumption 500mW (Max) Polarization	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 3.3A Power (Watts) No Load Power Consumption Folarization Applications Efficiency Operating Temperature O°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 24V 3.3A 79W Medical Folarization - Medical Level V Operating Temperature O°C ~ 60°C Output Connector DIN, 8 Pin 5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) Power (Watts) 79W No Load Power Consumption 500mW (Max) Polarization - Applications Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 3.3A 79W Medical Level V Operating Temperature 0°C ~ 60°C DIN, 8 Pin 5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Voltage - Input	85 ~ 264 VAC
Power (Watts) No Load Power Consumption 500mW (Max) Polarization Applications Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 79W Max 400mW (Max)	Voltage - Output	24V
No Load Power Consumption 500mW (Max) Polarization - Medical Efficiency Level V Operating Temperature 0° C $\sim 60^{\circ}$ C Output Connector DIN, 8 Pin Size / Dimension 5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Current - Output (Max)	3.3A
Polarization - Medical Medical Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 8 Pin Size / Dimension $5.19^{\circ}\text{L x } 3.07^{\circ}\text{W x } 1.34^{\circ}\text{H } (132.0 \text{mm x } 78.0 \text{mm x } 34.0 \text{mm})$	Power (Watts)	79W
ApplicationsMedicalEfficiencyLevel VOperating Temperature 0° C $\sim 60^{\circ}$ COutput ConnectorDIN, 8 PinSize / Dimension 5.19 " L x 3.07 " W x 1.34 " H (132.0 mm x 78.0 mm x 34.0 mm)	No Load Power Consumption	500mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 8 Pin Size / Dimension $5.19^{\circ}\text{L x } 3.07^{\circ}\text{W x } 1.34^{\circ}\text{H } (132.0\text{mm x } 78.0\text{mm x } 34.0\text{mm})$	Polarization	-
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 8 Pin Size / Dimension $5.19^{\circ}\text{L x } 3.07^{\circ}\text{W x } 1.34^{\circ}\text{H } (132.0\text{mm x } 78.0\text{mm x } 34.0\text{mm})$	Applications	Medical
Output Connector DIN, 8 Pin Size / Dimension 5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Efficiency	Level V
Size / Dimension 5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Operating Temperature	0°C ~ 60°C
	Output Connector	DIN, 8 Pin
Report errors?	Size / Dimension	5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)
		Report errors?

MWA080024A-12A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MWA080024A-12A Payment Methods



















MWA080024A-12A Shipping Methods













If you have any question about MWA080024A-12A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com