



#### MWA100012A-12A Information



For Reference Only

Part Number MWA100012A-12A Manufacturer Inventus Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 12V 100W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MWA100012A-12A Specifications**

Manufacturer Part Number         MWA 100012A-12A           Manufacturer         Inventus Power           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         MWA 100           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         85 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         8.3A           Power (Watts)         100W           No Load Power Consumption         500mW (Max)           Polarization         -           Applications         Medical           Efficiency         Level V           Operating Temperature         0°C ~ 60°C           Output Connector         DIN, 8 Pin           Size / Dimension         5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)    Report errors?			
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         MWA100           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         85 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         8.3A           Power (Watts)         100W           No Load Power Consumption         500mW (Max)           Polarization         -           Applications         Medical           Efficiency         Level V           Operating Temperature         0°C ~ 60°C           Output Connector         DIN, 8 Pin           Size / Dimension         5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Manufacturer Part Number	MWA100012A-12A	
Package         -           Series         MWA100           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         85 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         8.3A           Power (Watts)         100W           No Load Power Consumption         500mW (Max)           Polarization         -           Applications         Medical           Efficiency         Level V           Operating Temperature         0°C ~ 60°C           Output Connector         DIN, 8 Pin           Size / Dimension         5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Manufacturer	Inventus Power	
Package         -           Series         MWA100           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         85 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         8.3A           Power (Watts)         100W           No Load Power Consumption         500mW (Max)           Polarization         -           Applications         Medical           Efficiency         Level V           Operating Temperature         0°C ~ 60°C           Output Connector         DIN, 8 Pin           Size / Dimension         5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
SeriesMWA100Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input85 ~ 264 VACVoltage - Output12VCurrent - Output (Max)8.3APower (Watts)100WNo Load Power Consumption500mW (Max)Polarization-ApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 60°COutput ConnectorDIN, 8 PinSize / Dimension5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)		AC DC Desktop, Wall Adapters	
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 8.3A Power (Watts) 100W No Load Power Consumption 500mW (Max) Polarization - Applications Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Package	-	
Form Desktop (Class I) Input Type Cord (Sold Separately)  Voltage - Input 85 ~ 264 VAC  Voltage - Output 12V  Current - Output (Max) 8.3A  Power (Watts) 100W  No Load Power Consumption 500mW (Max)  Polarization - Applications Medical  Efficiency Level V  Operating Temperature 0°C ~ 60°C  Output Connector DIN, 8 Pin  Size / Dimension 5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Series	MWA100	
Input TypeCord (Sold Separately)Voltage - Input $85 \sim 264 \text{ VAC}$ Voltage - Output $12\text{V}$ Current - Output (Max) $8.3\text{A}$ Power (Watts) $100\text{W}$ No Load Power Consumption $500\text{mW}$ (Max)Polarization-ApplicationsMedicalEfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorDIN, 8 PinSize / Dimension $5.19^{\circ}\text{L x } 3.07^{\circ}\text{W x } 1.34^{\circ}\text{H } (132.0\text{mm x } 78.0\text{mm x } 34.0\text{mm})$	Region Utilized	International	
Voltage - Input $85 \sim 264 \text{ VAC}$ Voltage - Output $12\text{V}$ Current - Output (Max) $8.3\text{A}$ Power (Watts) $100\text{W}$ No Load Power Consumption $500\text{mW}$ (Max)Polarization-ApplicationsMedicalEfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorDIN, 8 PinSize / Dimension $5.19^{\circ}\text{L x } 3.07^{\circ}\text{W x } 1.34^{\circ}\text{H } (132.0\text{mm x } 78.0\text{mm x } 34.0\text{mm})$	Form	Desktop (Class I)	
Voltage - Output  Current - Output (Max)  8.3A  Power (Watts)  100W  No Load Power Consumption  Polarization  - Applications  Efficiency  Operating Temperature  O°C ~ 60°C  Output Connector  DIN, 8 Pin  Size / Dimension  12V  8.3A  100W  Max)  FOOMW (Max)  FOOMW (Max)  -  Wedical  Level V  Operating Temperature  O°C ~ 60°C  Output Connector  DIN, 8 Pin  5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Input Type	Cord (Sold Separately)	
Current - Output (Max)  8.3A  Power (Watts)  100W  No Load Power Consumption  500mW (Max)  Polarization  -  Applications  Medical  Efficiency  Level V  Operating Temperature  0°C ~ 60°C  Output Connector  DIN, 8 Pin  Size / Dimension  5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Voltage - Input	85 ~ 264 VAC	
Power (Watts) $100W$ No Load Power Consumption $500mW$ (Max)Polarization-ApplicationsMedicalEfficiencyLevel VOperating Temperature $0^{\circ}C \sim 60^{\circ}C$ Output ConnectorDIN, 8 PinSize / Dimension $5.19"$ L x $3.07"$ W x $1.34"$ H $(132.0mm$ x $78.0mm$ x $34.0mm$ )	Voltage - Output	12V	
No Load Power Consumption 500mW (Max)  Polarization - Medical  Efficiency Level V  Operating Temperature $0^{\circ}$ C $\sim 60^{\circ}$ C  Output Connector DIN, 8 Pin  Size / Dimension 5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Current - Output (Max)	8.3A	
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Power (Watts)	100W	
ApplicationsMedicalEfficiencyLevel VOperating Temperature $0^{\circ}$ C $\sim 60^{\circ}$ COutput ConnectorDIN, 8 PinSize / Dimension $5.19$ " L x $3.07$ " W x $1.34$ " H ( $132.0$ mm x $78.0$ mm x $34.0$ mm)	No Load Power Consumption	500mW (Max)	
Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 8 Pin  Size / Dimension $5.19^{\circ}\text{L x } 3.07^{\circ}\text{W x } 1.34^{\circ}\text{H } (132.0\text{mm x } 78.0\text{mm x } 34.0\text{mm})$	Polarization	-	
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 8 Pin Size / Dimension $5.19^{\circ}\text{L x } 3.07^{\circ}\text{W x } 1.34^{\circ}\text{H } (132.0\text{mm x } 78.0\text{mm x } 34.0\text{mm})$	Applications	Medical	
Output Connector         DIN, 8 Pin           Size / Dimension         5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Efficiency	Level V	
Size / Dimension 5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	Operating Temperature	0°C ~ 60°C	
	Output Connector	DIN, 8 Pin	
Report errors?	Size / Dimension	5.19" L x 3.07" W x 1.34" H (132.0mm x 78.0mm x 34.0mm)	
		Rep	ort errors?

#### **MWA100012A-12A Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **MWA100012A-12A Payment Methods**



















### **MWA100012A-12A Shipping Methods**













If you have any question about MWA100012A-12A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com