



MX1.5KE18CA Information

Heisener.com

Part Number MX1.5KE18CA

Manufacturer Microsemi Corporation

Category Circuit Protection

TVS - Diodes

Description TVS DIODE 15.3VWM 25.2VC CASE1

Package DO-201AA, DO-27, Axial

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MX1.5KE18CA Specifications

Manufacturer Part Number MX1.5KE18CA Manufacturer Microsemi Corporation Category Circuit Protection Package DO-201AA, DO-27, Axial Series Military, MIL-PRF-19500 Type Zener Unidirectional Channels - Bidirectional Channels 1 Voltage - Reverse Standoff (Typ) 15.3V Voltage - Breakdown (Min) 17.1V Voltage - Clamping (Max) @ Ipp 25.2V Current - Peak Pulse (10/1000µs) 59.5A Power - Peak Pulse Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -65°C ~ 150°C (TI) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package CASE-1		
Category Circuit Protection TVS - Diodes Package DO-201AA, DO-27, Axial Series Military, MIL-PRF-19500 Type Zener Unidirectional Channels - Bidirectional Channels 1 Voltage - Reverse Standoff (Typ) 15.3V Voltage - Breakdown (Min) 17.1V Voltage - Clamping (Max) @ Ipp 25.2V Current - Peak Pulse (10/1000μs) 59.5A Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package CASE-1	Manufacturer Part Number	MX1.5KE18CA
TVS - DiodesPackageDO-201AA, DO-27, AxialSeriesMilitary, MIL-PRF-19500TypeZenerUnidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)15.3VVoltage - Breakdown (Min)17.1VVoltage - Clamping (Max) @ Ipp25.2VCurrent - Peak Pulse (10/1000μs)59.5APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 150°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device PackageCASE-1	Manufacturer	Microsemi Corporation
PackageDO-201AA, DO-27, AxialSeriesMilitary, MIL-PRF-19500TypeZenerUnidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)15.3VVoltage - Breakdown (Min)17.1VVoltage - Clamping (Max) @ Ipp25.2VCurrent - Peak Pulse (10/1000µs)59.5APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 150°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device PackageCASE-1	Category	Circuit Protection
SeriesMilitary, MIL-PRF-19500TypeZenerUnidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)15.3VVoltage - Breakdown (Min)17.1VVoltage - Clamping (Max) @ Ipp25.2VCurrent - Peak Pulse (10/1000μs)59.5APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 150°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device PackageCASE-1		TVS - Diodes
Type Zener Unidirectional Channels - Bidirectional Channels 1 Voltage - Reverse Standoff (Typ) 15.3V Voltage - Breakdown (Min) 17.1V Voltage - Clamping (Max) @ Ipp 25.2V Current - Peak Pulse (10/1000µs) 59.5A Power - Peak Pulse (10/1000µs) 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package	Package	DO-201AA, DO-27, Axial
Unidirectional Channels Bidirectional Channels 1 Voltage - Reverse Standoff (Typ) 15.3V Voltage - Breakdown (Min) 17.1V Voltage - Clamping (Max) @ Ipp 25.2V Current - Peak Pulse (10/1000µs) 59.5A Power - Peak Pulse (10/1000µs) Power Line Protection Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package	Series	Military, MIL-PRF-19500
Bidirectional Channels Voltage - Reverse Standoff (Typ) 15.3V Voltage - Breakdown (Min) 17.1V Voltage - Clamping (Max) @ Ipp 25.2V Current - Peak Pulse (10/1000µs) 59.5A Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature 65°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package	Type	Zener
Voltage - Reverse Standoff (Typ) Voltage - Breakdown (Min) 17.1V Voltage - Clamping (Max) @ Ipp 25.2V Current - Peak Pulse (10/1000µs) Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package	Unidirectional Channels	-
Voltage - Breakdown (Min) Voltage - Clamping (Max) @ Ipp 25.2V Current - Peak Pulse (10/1000μs) Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package CASE-1	Bidirectional Channels	1
Voltage - Clamping (Max) @ Ipp 25.2V Current - Peak Pulse (10/1000μs) 59.5A Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package CASE-1	Voltage - Reverse Standoff (Typ)	15.3V
Current - Peak Pulse (10/1000μs)59.5APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 150°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device PackageCASE-1	Voltage - Breakdown (Min)	17.1V
Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package CASE-1	Voltage - Clamping (Max) @ Ipp	25.2V
Power Line Protection Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package	Current - Peak Pulse (10/1000µs)	59.5A
Applications Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package CASE-1	Power - Peak Pulse	1500W (1.5kW)
Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package CASE-1	Power Line Protection	No
Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package CASE-1	Applications	General Purpose
Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package CASE-1	Capacitance @ Frequency	-
Package / Case DO-201AA, DO-27, Axial Supplier Device Package CASE-1	Operating Temperature	-65°C ~ 150°C (TJ)
Supplier Device Package CASE-1	Mounting Type	Through Hole
	Package / Case	DO-201AA, DO-27, Axial
Report errors?	Supplier Device Package	CASE-1
		Report errors?

MX1.5KE18CA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MX1.5KE18CA Payment Methods





















MX1.5KE18CA Shipping Methods













If you have any question about MX1.5KE18CA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com