



MXLSMBG33A Information



For Reference Only

Part Number MXLSMBG33A Manufacturer Microsemi Corporation Category

Circuit Protection TVS - Diodes

Description TVS DIODE 33VWM 53.3VC DO215AA

Package DO-215AA, SMB Gull Wing

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MXLSMBG33A Specifications

Manufacturer Part Number MXLSMBG33A Manufacturer Microsemi Corporation Category Circuit Protection TVS - Diodes Package DO-215AA, SMB Gull Wing Series Military, MIL-PRF-19500 Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 33V Voltage - Breakdown (Min) 36.7V Voltage - Clamping (Max) @ Ipp 53.3V Current - Peak Pulse (10/1000µs) 11.3A Power - Peak Pulse (10/1000µs) 600W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-215AA, SMB Gull Wing Supplier Device Package SMBG (DO-215AA)	-	
Category Circuit Protection TVS - Diodes Package DO-215AA, SMB Gull Wing Series Military, MIL-PRF-19500 Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 33V Voltage - Breakdown (Min) 36.7V Voltage - Clamping (Max) @ Ipp 53.3V Current - Peak Pulse (10/1000µs) 11.3A Power - Peak Pulse 600W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-215AA, SMB Gull Wing Supplier Device Package SMBG (DO-215AA)	Manufacturer Part Number	MXLSMBG33A
TVS - Diodes Package DO-215AA, SMB Gull Wing Series Military, MIL-PRF-19500 Type Zener Unidirectional Channels I Bidirectional Channels - Voltage - Reverse Standoff (Typ) 33V Voltage - Breakdown (Min) 36.7V Voltage - Clamping (Max) @ Ipp 53.3V Current - Peak Pulse (10/1000μs) 11.3A Power - Peak Pulse 600W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-215AA, SMB Gull Wing Supplier Device Package	Manufacturer	Microsemi Corporation
PackageDO-215AA, SMB Gull WingSeriesMilitary, MIL-PRF-19500TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)33VVoltage - Breakdown (Min)36.7VVoltage - Clamping (Max) @ Ipp53.3VCurrent - Peak Pulse (10/1000μs)11.3APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-215AA, SMB Gull WingSupplier Device PackageSMBG (DO-215AA)	Category	Circuit Protection
SeriesMilitary, MIL-PRF-19500TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)33VVoltage - Breakdown (Min)36.7VVoltage - Clamping (Max) @ Ipp53.3VCurrent - Peak Pulse (10/1000μs)11.3APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-215AA, SMB Gull WingSupplier Device PackageSMBG (DO-215AA)		TVS - Diodes
Type Zener Unidirectional Channels Bidirectional Channels - Voltage - Reverse Standoff (Typ) 33V Voltage - Breakdown (Min) 36.7V Voltage - Clamping (Max) @ Ipp 53.3V Current - Peak Pulse (10/1000µs) 11.3A Power - Peak Pulse 600W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-215AA, SMB Gull Wing Supplier Device Package	Package	DO-215AA, SMB Gull Wing
Unidirectional Channels Bidirectional Channels Voltage - Reverse Standoff (Typ) 33V Voltage - Breakdown (Min) 36.7V Voltage - Clamping (Max) @ Ipp 53.3V Current - Peak Pulse (10/1000µs) 11.3A Power - Peak Pulse 600W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-215AA, SMB Gull Wing Supplier Device Package SMBG (DO-215AA)	Series	Military, MIL-PRF-19500
Bidirectional Channels Voltage - Reverse Standoff (Typ) 33V Voltage - Breakdown (Min) 36.7V Voltage - Clamping (Max) @ Ipp 53.3V Current - Peak Pulse (10/1000μs) 11.3A Power - Peak Pulse 600W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-215AA, SMB Gull Wing Supplier Device Package SMBG (DO-215AA)	Туре	Zener
Voltage - Reverse Standoff (Typ)33VVoltage - Breakdown (Min)36.7VVoltage - Clamping (Max) @ Ipp53.3VCurrent - Peak Pulse (10/1000μs)11.3APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-215AA, SMB Gull WingSupplier Device PackageSMBG (DO-215AA)	Unidirectional Channels	1
Voltage - Breakdown (Min) Voltage - Clamping (Max) @ Ipp 53.3V Current - Peak Pulse (10/1000μs) 11.3A Power - Peak Pulse 600W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-215AA, SMB Gull Wing Supplier Device Package SMBG (DO-215AA)	Bidirectional Channels	-
Voltage - Clamping (Max) @ Ipp 53.3V Current - Peak Pulse (10/1000μs) 11.3A Power - Peak Pulse 600W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-215AA, SMB Gull Wing Supplier Device Package	Voltage - Reverse Standoff (Typ)	33V
Current - Peak Pulse (10/1000μs)11.3APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-215AA, SMB Gull WingSupplier Device PackageSMBG (DO-215AA)	Voltage - Breakdown (Min)	36.7V
Power - Peak Pulse 600W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-215AA, SMB Gull Wing Supplier Device Package SMBG (DO-215AA)	Voltage - Clamping (Max) @ Ipp	53.3V
Power Line Protection Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-215AA, SMB Gull Wing Supplier Device Package SMBG (DO-215AA)	Current - Peak Pulse (10/1000µs)	11.3A
Applications Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-215AA, SMB Gull Wing Supplier Device Package SMBG (DO-215AA)	Power - Peak Pulse	600W
Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-215AA, SMB Gull Wing Supplier Device Package SMBG (DO-215AA)	Power Line Protection	No
Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-215AA, SMB Gull Wing Supplier Device Package SMBG (DO-215AA)	Applications	General Purpose
Mounting Type Surface Mount Package / Case DO-215AA, SMB Gull Wing Supplier Device Package SMBG (DO-215AA)	Capacitance @ Frequency	-
Package / Case DO-215AA, SMB Gull Wing Supplier Device Package SMBG (DO-215AA)	Operating Temperature	-65°C ~ 150°C (TJ)
Supplier Device Package SMBG (DO-215AA)	Mounting Type	Surface Mount
	Package / Case	DO-215AA, SMB Gull Wing
Report errors?	Supplier Device Package	SMBG (DO-215AA)
		Report errors?

MXLSMBG33A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MXLSMBG33A Payment Methods





















MXLSMBG33A Shipping Methods













If you have any question about MXLSMBG33A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com