

MXLSMCJLCE75AE3

MXLSMCJLCE75AE3 Information



For Reference Only

Part NumberMXLSMCJLCE75AE3ManufacturerMicrosemi CorporationCategoryCircuit Protection

TVS - Diodes

Description TVS DIODE 75VWM 121VC DO214AB

Package DO-214AB, SMC

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MXLSMCJLCE75AE3 Specifications

| Manufacturer Part Number MXLSMCJLCE75AE3 Manufacturer Microsemi Corporation Category Circuit Protection TVS - Diodes Package DO-214AB, SMC Series Military, MIL-PRF-19500 Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 75V Voltage - Breakdown (Min) 83.3V Voltage - Clamping (Max) @ Ipp 121V Current - Peak Pulse (10/1000μs) 12.4A Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency 90pF @ IMHz Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AB, SMC Supplier Device Package DO-214AB (SMCJ) | _ | |
|--|----------------------------------|-------------------------|
| Category Circuit Protection TVS - Diodes Package DO-214AB, SMC Series Military, MIL-PRF-19500 Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 75V Voltage - Breakdown (Min) 83.3V Voltage - Clamping (Max) @ Ipp 121V Current - Peak Pulse (10/1000µs) 12.4A Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency 90pF @ 1MHz Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AB, SMC Supplier Device Package DO-214AB (SMCJ) | Manufacturer Part Number | MXLSMCJLCE75AE3 |
| TVS - Diodes Package DO-214AB, SMC Series Military, MIL-PRF-19500 Type Zener Unidirectional Channels I Bidirectional Channels - Voltage - Reverse Standoff (Typ) 75V Voltage - Breakdown (Min) 83.3V Voltage - Clamping (Max) @ Ipp 121V Current - Peak Pulse (10/1000μs) 12.4A Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case Supplier Device Package | Manufacturer | Microsemi Corporation |
| PackageDO-214AB, SMCSeriesMilitary, MIL-PRF-19500TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)75VVoltage - Breakdown (Min)83.3VVoltage - Clamping (Max) @ Ipp121VCurrent - Peak Pulse (10/1000μs)12.4APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency90pF @ 1MHzOperating Temperature-65°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-214AB, SMCSupplier Device PackageDO-214AB (SMCJ) | Category | Circuit Protection |
| Series Military, MIL-PRF-19500 Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 75V Voltage - Breakdown (Min) 83.3V Voltage - Clamping (Max) @ Ipp 121V Current - Peak Pulse (10/1000µs) 12.4A Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency 90pF @ 1MHz Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AB, SMC Supplier Device Package | | TVS - Diodes |
| Type Zener Unidirectional Channels Bidirectional Channels - Voltage - Reverse Standoff (Typ) 75V Voltage - Breakdown (Min) 83.3V Voltage - Clamping (Max) @ Ipp 121V Current - Peak Pulse (10/1000µs) 12.4A Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency 90pF @ 1MHz Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AB, SMC Supplier Device Package | Package | DO-214AB, SMC |
| Unidirectional Channels Bidirectional Channels - Voltage - Reverse Standoff (Typ) 75V Voltage - Breakdown (Min) 83.3V Voltage - Clamping (Max) @ Ipp 121V Current - Peak Pulse (10/1000µs) Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency 90pF @ 1MHz Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AB, SMC Supplier Device Package | Series | Military, MIL-PRF-19500 |
| Bidirectional Channels Voltage - Reverse Standoff (Typ) 75V Voltage - Breakdown (Min) 83.3V Voltage - Clamping (Max) @ Ipp 121V Current - Peak Pulse (10/1000µs) 12.4A Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency 90pF @ 1MHz Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AB, SMC Supplier Device Package | Туре | Zener |
| Voltage - Reverse Standoff (Typ) Voltage - Breakdown (Min) 83.3V Voltage - Clamping (Max) @ Ipp 121V Current - Peak Pulse (10/1000µs) Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AB, SMC Supplier Device Package | Unidirectional Channels | 1 |
| Voltage - Breakdown (Min) Voltage - Clamping (Max) @ Ipp 121V Current - Peak Pulse (10/1000μs) Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency 90pF @ 1MHz Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AB, SMC Supplier Device Package | Bidirectional Channels | - |
| Voltage - Clamping (Max) @ Ipp121VCurrent - Peak Pulse (10/1000μs)12.4APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency90pF @ 1MHzOperating Temperature-65°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-214AB, SMCSupplier Device PackageDO-214AB (SMCJ) | Voltage - Reverse Standoff (Typ) | 75V |
| Current - Peak Pulse (10/1000µs) 12.4A Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency 90pF @ 1MHz Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AB, SMC Supplier Device Package | Voltage - Breakdown (Min) | 83.3V |
| Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency 90pF @ 1MHz Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AB, SMC Supplier Device Package DO-214AB (SMCJ) | Voltage - Clamping (Max) @ Ipp | 121V |
| Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency90pF @ 1MHzOperating Temperature-65°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-214AB, SMCSupplier Device PackageDO-214AB (SMCJ) | Current - Peak Pulse (10/1000µs) | 12.4A |
| Applications General Purpose Capacitance @ Frequency 90pF @ 1MHz Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AB, SMC Supplier Device Package DO-214AB (SMCJ) | Power - Peak Pulse | 1500W (1.5kW) |
| Capacitance @ Frequency 90pF @ 1MHz Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AB, SMC Supplier Device Package DO-214AB (SMCJ) | Power Line Protection | No |
| Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AB, SMC Supplier Device Package DO-214AB (SMCJ) | Applications | General Purpose |
| Mounting Type Surface Mount Package / Case DO-214AB, SMC Supplier Device Package DO-214AB (SMCJ) | Capacitance @ Frequency | 90pF @ 1MHz |
| Package / Case DO-214AB, SMC Supplier Device Package DO-214AB (SMCJ) | Operating Temperature | -65°C ~ 150°C (TJ) |
| Supplier Device Package DO-214AB (SMCJ) | Mounting Type | Surface Mount |
| | Package / Case | DO-214AB, SMC |
| | Supplier Device Package | DO-214AB (SMCJ) |
| Report errors? | | Report errors? |

MXLSMCJLCE75AE3 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MXLSMCJLCE75AE3 Payment Methods



















MXLSMCJLCE75AE3 Shipping Methods













If you have any question about MXLSMCJLCE75AE3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com