



MXLSMLG15A Information

Heisener.com

For Reference Only

Part Number MXLSMLG15A

TVS - Diodes

Manufacturer Microsemi Corporation

Category

Circuit Protection

Description

TVS DIODE 15VWM 24.4VC DO215AB

Package

DO-215AB, SMC Gull Wing

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MXLSMLG15A Specifications

Manufacturer Part NumberMXLSMLG15AManufacturerMicrosemi CorporationCategoryCircuit ProtectionPackageDO-215AB, SMC Gull WingSeriesMilitary, MIL-PRF-19500TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)15VVoltage - Breakdown (Min)16.7VVoltage - Clamping (Max) @ Ipp24.4VCurrent - Peak Pulse (10/1000μs)123APower - Peak Pulse3000W (3kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-215AB, SMC Gull WingSupplier Device PackageSMLG (DO-215AB)	The state of the s	
Category Circuit Protection TVS - Diodes Package DO-215AB, SMC Gull Wing Series Military, MIL-PRF-19500 Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 15V Voltage - Breakdown (Min) 16.7V Voltage - Clamping (Max) @ Ipp 24.4V Current - Peak Pulse (10/1000µs) 123A Power - Peak Pulse 3000W (3kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-215AB, SMC Gull Wing	Manufacturer Part Number	MXLSMLG15A
TVS - Diodes Package DO-215AB, SMC Gull Wing Series Military, MIL-PRF-19500 Type Zener Unidirectional Channels Bidirectional Channels - Voltage - Reverse Standoff (Typ) 15V Voltage - Breakdown (Min) 16.7V Voltage - Clamping (Max) @ Ipp 24.4V Current - Peak Pulse (10/1000μs) 123A Power - Peak Pulse 3000W (3kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-215AB, SMC Gull Wing	Manufacturer	Microsemi Corporation
PackageDO-215AB, SMC Gull WingSeriesMilitary, MIL-PRF-19500TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)15VVoltage - Breakdown (Min)16.7VVoltage - Clamping (Max) @ Ipp24.4VCurrent - Peak Pulse (10/1000μs)123APower - Peak Pulse3000W (3kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-215AB, SMC Gull Wing	Category	Circuit Protection
SeriesMilitary, MIL-PRF-19500TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)15VVoltage - Breakdown (Min)16.7VVoltage - Clamping (Max) @ Ipp24.4VCurrent - Peak Pulse (10/1000μs)123APower - Peak Pulse3000W (3kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-215AB, SMC Gull Wing		TVS - Diodes
TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)15VVoltage - Breakdown (Min)16.7VVoltage - Clamping (Max) @ Ipp24.4VCurrent - Peak Pulse (10/1000μs)123APower - Peak Pulse3000W (3kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-215AB, SMC Gull Wing	Package	DO-215AB, SMC Gull Wing
Unidirectional Channels Bidirectional Channels - Voltage - Reverse Standoff (Typ) 15V Voltage - Breakdown (Min) 16.7V Voltage - Clamping (Max) @ Ipp 24.4V Current - Peak Pulse (10/1000µs) Power - Peak Pulse 3000W (3kW) Power Line Protection Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-215AB, SMC Gull Wing	Series	Military, MIL-PRF-19500
Bidirectional Channels Voltage - Reverse Standoff (Typ) 15V Voltage - Breakdown (Min) 16.7V Voltage - Clamping (Max) @ Ipp 24.4V Current - Peak Pulse (10/1000μs) 123A Power - Peak Pulse 3000W (3kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-215AB, SMC Gull Wing	Туре	Zener
Voltage - Reverse Standoff (Typ)15VVoltage - Breakdown (Min)16.7VVoltage - Clamping (Max) @ Ipp24.4VCurrent - Peak Pulse (10/1000μs)123APower - Peak Pulse3000W (3kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-215AB, SMC Gull Wing	Unidirectional Channels	1
Voltage - Breakdown (Min)16.7VVoltage - Clamping (Max) @ Ipp24.4VCurrent - Peak Pulse (10/1000μs)123APower - Peak Pulse3000W (3kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-215AB, SMC Gull Wing	Bidirectional Channels	-
Voltage - Clamping (Max) @ Ipp24.4VCurrent - Peak Pulse (10/1000μs)123APower - Peak Pulse3000W (3kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-215AB, SMC Gull Wing	Voltage - Reverse Standoff (Typ)	15V
Current - Peak Pulse (10/1000μs)123APower - Peak Pulse3000W (3kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-215AB, SMC Gull Wing	Voltage - Breakdown (Min)	16.7V
Power - Peak Pulse3000W (3kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-215AB, SMC Gull Wing	Voltage - Clamping (Max) @ Ipp	24.4V
Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-215AB, SMC Gull Wing	Current - Peak Pulse (10/1000µs)	123A
Applications Capacitance @ Frequency Operating Temperature Mounting Type Surface Mount Package / Case General Purpose -65°C ~ 150°C (TJ) Surface Mount DO-215AB, SMC Gull Wing	Power - Peak Pulse	3000W (3kW)
Capacitance @ Frequency - Operating Temperature -65°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-215AB, SMC Gull Wing	Power Line Protection	No
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C} \text{ (TJ)}$ Mounting Type Surface Mount Package / Case DO-215AB, SMC Gull Wing	Applications	General Purpose
Mounting Type Surface Mount Package / Case DO-215AB, SMC Gull Wing	Capacitance @ Frequency	-
Package / Case DO-215AB, SMC Gull Wing	Operating Temperature	-65°C ~ 150°C (TJ)
•	Mounting Type	Surface Mount
Supplier Device Package SMLG (DO-215AB)	Package / Case	DO-215AB, SMC Gull Wing
	Supplier Device Package	SMLG (DO-215AB)
Report errors?		Report errors?

MXLSMLG15A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MXLSMLG15A Payment Methods





















MXLSMLG15A Shipping Methods













If you have any question about MXLSMLG15A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com