

MY2 AC6 (S) Information

For Reference Only

Part Number MY2 AC6 (S)

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GENERAL PURPOSE DPDT 5A 6V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MY2 AC6 (S) Specifications

Manufacturer Part NumberMY2 AC6 (S)ManufacturerOmron Automation and SafetyCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current183mACoil Voltage6VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)4.8 VACTurn Off Voltage (Min)1.8 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketable		
Category Relays Power Relays, Over 2 Amps Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 183mA Coil Voltage 6VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.8 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 20ms Release Time 20ms Features -	Manufacturer Part Number	MY2 AC6 (S)
Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 183mA Coil Voltage 6VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.8 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 20ms Release Time 20ms Features -	Manufacturer	Omron Automation and Safety
Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 183mA Coil Voltage 6VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.8 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 20ms Release Time 20ms Features -	Category	Relays
SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current183mACoil Voltage6VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)4.8 VACTurn Off Voltage (Min)1.8 VACOperate Time20msRelease Time20msFeatures-		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 183mA Coil Voltage 6VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.8 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 20ms Release Time 20ms Features -	Package	-
Coil TypeNon LatchingCoil Current183mACoil Voltage6VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)4.8 VACTurn Off Voltage (Min)1.8 VACOperate Time20msRelease Time20msFeatures-	Series	MY
Coil Current 183mA Coil Voltage 6VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.8 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 20ms Release Time 20ms Features -	Relay Type	General Purpose
Coil Voltage 6VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.8 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 20ms Release Time 20ms Features -	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.8 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 20ms Release Time 20ms Features -	Coil Current	183mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.8 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 20ms Release Time 20ms Features -	Coil Voltage	6VAC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.8 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 20ms Release Time 20ms Features -	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time 20ms Features -	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features -	Switching Voltage	250VAC, 125VDC - Max
Operate Time 20ms Release Time 20ms Features -	Turn On Voltage (Max)	4.8 VAC
Release Time 20ms Features -	Turn Off Voltage (Min)	1.8 VAC
Features -	Operate Time	20ms
	Release Time	20ms
Mounting Type Socketable	Features	-
Bockettore	Mounting Type	Socketable
Termination Style Plug In	Termination Style	Plug In
Report errors?		Report errors?

MY2 AC6 (S) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MY2 AC6 (S) Payment Methods



















MY2 AC6 (S) Shipping Methods













If you have any question about MY2 AC6 (S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com