

MY2 DC12 (S) Information



For Reference Only

Part Number MY2 DC12 (S)

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MY2 DC12 (S) Specifications

Manufacturer Part NumberMY2 DC12 (8)ManufacturerOmron Automation and SafetyCategoryRelaysPackage-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	MY2 DC12 (S)
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Series	MY
Coil Current 75mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features Mounting Type Socketable Termination Style Plug In	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style	Coil Current	75mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style	Coil Voltage	12VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 7 Turn Off Voltage (Min) 9.6 VDC 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style 1.2 VDC 20ms Soketable Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	9.6 VDC
Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	1.2 VDC
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

MY2 DC12 (S) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MY2 DC12 (S) Payment Methods





















MY2 DC12 (S) Shipping Methods













If you have any question about MY2 DC12 (S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com