



### **MY2K DC48 Information**



For Reference Only

Part Number MY2K DC48

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPDT 3A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MY2K DC48 Specifications**

Manufacturer Part Number       MY2K DC48         Manufacturer       Omron Automation and Safety         Category       Relays         Power Relays, Over 2 Amps         Package       -         Series       MYK         Relay Type       General Purpose         Coil Type       Latching, Dual Coil         Coil Current       27mA         Coil Voltage       48VDC         Contact Form       DPDT (2 Form C)         Contact Rating (Current)       3A         Switching Voltage       250VAC, 125VDC - Max         Turn On Voltage (Max)       38.4 VDC         Turn Off Voltage (Min)       -         Operate Time       15ms         Release Time       15ms         Features       -         Mounting Type       Socketable         Termination Style       Plug In		
CategoryRelaysPackage-SeriesMYKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current27mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	MY2K DC48
Package - Series MYK Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 27mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Purpose MYK General Purpose General Purpose MYK General Purpose 12th N Seneral	Manufacturer	Omron Automation and Safety
Package         -           Series         MYK           Relay Type         General Purpose           Coil Type         Latching, Dual Coil           Coil Current         27mA           Coil Voltage         48VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         3A           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         38.4 VDC           Turn Off Voltage (Min)         -           Operate Time         15ms           Release Time         15ms           Features         -           Mounting Type         Socketable           Termination Style         Plug In	Category	Relays
SeriesMYKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current27mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current27mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In	Package	-
Coil TypeLatching, Dual CoilCoil Current27mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In	Series	MYK
Coil Current27mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In	Coil Type	Latching, Dual Coil
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  38.4 VDC  Turn Off Voltage (Min)  Operate Time  15ms  Release Time  15ms  Release Time  5 cocketable  Termination Style  Plug In	Coil Current	27mA
Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  38.4 VDC  Turn Off Voltage (Min)  Operate Time  15ms  Release Time  15ms  Features  - Mounting Type  Socketable  Termination Style  Plug In	Coil Voltage	48VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  15ms  Release Time  15ms  Features  - Mounting Type  Socketable  Termination Style  38.4 VDC  -  15ms  15ms  Plug In	Contact Rating (Current)	3A
Turn Off Voltage (Min)  Operate Time  15ms  Release Time  15ms  Features  - Mounting Type  Socketable  Termination Style  Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	38.4 VDC
Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	-
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	15ms
Mounting Type Socketable Termination Style Plug In	Release Time	15ms
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
Report chois:		Report errors?

#### **MY2K DC48 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **MY2K DC48 Payment Methods**



















## **MY2K DC48 Shipping Methods**













If you have any question about MY2K DC48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com