



## MY2N AC200/220 (S) Information



For Reference Only

Part Number MY2N AC200/220 (S)

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPDT 5A 220V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## MY2N AC200/220 (S) Specifications

Manufacturer       MY2N AC200/220 (\$)         Manufacturer       Omron Automation and Safety         Category       Relays         Power Relays, Over 2 Amps         Package       -         Series       MY         Relay Type       General Purpose         Coil Type       Non Latching         Coil Current       4.6mA         Coil Voltage       220VAC         Contact Form       DPDT (2 Form C)         Contact Rating (Current)       5A         Switching Voltage       250VAC, 125VDC - Max         Turn On Voltage (Max)       176 VAC         Turn Off Voltage (Min)       66 VAC         Operate Time       20ms         Release Time       20ms         Features       LED Indicator         Mounting Type       Socketable         Termination Style       Plug In		
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         MY           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         4.6mA           Coil Voltage         220VAC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         5A           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         176 VAC           Turn Off Voltage (Min)         66 VAC           Operate Time         20ms           Release Time         20ms           Features         LED Indicator           Mounting Type         Socketable           Termination Style         Plug In	Manufacturer Part Number	MY2N AC200/220 (S)
Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 4.6mA Coil Voltage 220VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style	Manufacturer	Omron Automation and Safety
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.6mACoil Voltage220VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Category	Relays
SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.6mACoil Voltage220VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 4.6mA Coil Voltage 220VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Release Time LED Indicator Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current4.6mACoil Voltage220VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Series	MY
Coil Current4.6mACoil Voltage220VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage 220VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  176 VAC  Turn Off Voltage (Min)  66 VAC  Operate Time  20ms  Release Time  20ms  Release Time  LED Indicator  Mounting Type  Socketable  Termination Style	Coil Current	4.6mA
Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  176 VAC  Turn Off Voltage (Min)  66 VAC  Operate Time  20ms  Release Time  20ms  Features  LED Indicator  Mounting Type  Socketable  Termination Style	Coil Voltage	220VAC
Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 176 VAC  Turn Off Voltage (Min) 66 VAC  Operate Time 20ms  Release Time 20ms  Features LED Indicator  Mounting Type Socketable  Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  176 VAC  Turn Off Voltage (Min)  66 VAC  Operate Time  20ms  Release Time  20ms  Features  LED Indicator  Mounting Type  Socketable  Termination Style  176 VAC	Contact Rating (Current)	5A
Turn Off Voltage (Min)  Operate Time  20ms  Release Time  20ms  Features  LED Indicator  Mounting Type  Socketable  Termination Style  Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	176 VAC
Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	66 VAC
Features LED Indicator  Mounting Type Socketable  Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	LED Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

### MY2N AC200/220 (S) Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MY2N AC200/220 (S) Payment Methods



















### MY2N AC200/220 (S) Shipping Methods













If you have any question about MY2N AC200/220 (S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com