

Heisener.com

MY2N-CR AC110/120 (S)

MY2N-CR AC110/120 (S) Information

Part Number MY2N-CR AC110/120 (S)

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 120V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MY2N-CR AC110/120 (S) Specifications

Manufacturer Part Number MY2N-CR AC110/120 (\$) Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 8.4mA Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In		
Category Relays Power Relays, Over 2 Amps Package	Manufacturer Part Number	MY2N-CR AC110/120 (S)
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.4mACoil Voltage120VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time20msRelease Time20msFeaturesLED Indicator, RC CircuitMounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.4mACoil Voltage120VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time20msRelease Time20msFeaturesLED Indicator, RC CircuitMounting TypeSocketableTermination StylePlug In	Category	Relays
SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.4mACoil Voltage120VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time20msRelease Time20msFeaturesLED Indicator, RC CircuitMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 8.4mA Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current8.4mACoil Voltage120VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time20msRelease Time20msFeaturesLED Indicator, RC CircuitMounting TypeSocketableTermination StylePlug In	Series	MY
Coil Current Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In	Coil Current	8.4mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In	Coil Voltage	120VAC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 70 Voltage (Min) 60 VAC 70 Operate Time 70 Coms 70 Release Time 70 Coms 70 Coms 70 LED Indicator, RC Circuit 70 Mounting Type 70 Socketable 70 Termination Style 71 Plug In	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 20ms Release Time 20ms Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	96 VAC
Release Time 20ms Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	36 VAC
Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	LED Indicator, RC Circuit
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

MY2N-CR AC110/120 (S) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MY2N-CR AC110/120 (S) Payment Methods


































If you have any question about MY2N-CR AC110/120 (S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com