

MY4 AC24 (S) Information



For Reference Only

Part Number MY4 AC24 (S)

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 3A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MY4 AC24 (S) Specifications

Manufacturer Part Number MY4 AC24 (8) Manufacturer Omron Automation and Safety Category Relays Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 46mA Coil Voltage 24VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current46mACoil Voltage24VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	MY4 AC24 (S)
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current46mACoil Voltage24VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 46mA Coil Voltage 24VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current46mACoil Voltage24VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 46mA Coil Voltage 24VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 20ms Release Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current46mACoil Voltage24VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Series	MY
Coil Current 46mA Coil Voltage 24VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Relay Type	General Purpose
Coil Voltage 24VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Coil Current	46mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Coil Voltage	24VAC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style 19.2 VAC 7.2 VAC Plug In	Contact Rating (Current)	3A
Turn Off Voltage (Min) 7.2 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	19.2 VAC
Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	7.2 VAC
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

MY4 AC24 (S) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MY4 AC24 (S) Payment Methods



















MY4 AC24 (S) Shipping Methods













If you have any question about MY4 AC24 (S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com