

## MY4 AC6 (S) Information

Heisener.com

Part Number MY4 AC6 (S)

Manufacturer Omron Automation and Safety

Category

Power Relays, Over 2 Amps

**Description** RELAY GENERAL PURPOSE 4PDT 3A 6V

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MY4 AC6 (S) Specifications

Manufacturer Part NumberMY4 AC6 (S)ManufacturerOmron Automation and SafetyCategoryRelaysPackage-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current183mACoil Voltage6VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)4.8 VACTurn Off Voltage (Min)1.8 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In		
Category         Relays           Package         -           Series         MY           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         183mA           Coil Voltage         6VAC           Contact Form         4PDT (4 Form C)           Contact Rating (Current)         3A           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         4.8 VAC           Turn Off Voltage (Min)         1.8 VAC           Operate Time         20ms           Release Time         20ms           Features         -           Mounting Type         Socketable           Termination Style         Plug In	Manufacturer Part Number	MY4 AC6 (S)
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current183mACoil Voltage6VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)4.8 VACTurn Off Voltage (Min)1.8 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package         -           Series         MY           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         183mA           Coil Voltage         6VAC           Contact Form         4PDT (4 Form C)           Contact Rating (Current)         3A           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         4.8 VAC           Turn Off Voltage (Min)         1.8 VAC           Operate Time         20ms           Release Time         20ms           Features         -           Mounting Type         Socketable           Termination Style         Plug In	Category	Relays
SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current183mACoil Voltage6VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)4.8 VACTurn Off Voltage (Min)1.8 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 183mA Coil Voltage 6VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.8 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current183mACoil Voltage6VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)4.8 VACTurn Off Voltage (Min)1.8 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Series	MY
Coil Current Coil Voltage 6VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.8 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Relay Type	General Purpose
Coil Voltage6VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)4.8 VACTurn Off Voltage (Min)1.8 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C)  Contact Rating (Current) 3A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 4.8 VAC  Turn Off Voltage (Min) 1.8 VAC  Operate Time 20ms  Release Time 20ms  Features - Mounting Type Socketable  Termination Style Plug In	Coil Current	183mA
Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  4.8 VAC  Turn Off Voltage (Min)  1.8 VAC  Operate Time  20ms  Release Time  20ms  Features  - Mounting Type  Socketable  Termination Style  Plug In	Coil Voltage	6VAC
Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 4.8 VAC  Turn Off Voltage (Min) 1.8 VAC  Operate Time 20ms  Release Time 20ms  Features -  Mounting Type Socketable  Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max)  4.8 VAC  Turn Off Voltage (Min)  1.8 VAC  Operate Time  20ms  Release Time  20ms  Features  - Mounting Type Socketable  Termination Style  4.8 VAC	Contact Rating (Current)	3A
Turn Off Voltage (Min)  Operate Time  20ms  Release Time  20ms  Features  - Mounting Type  Socketable  Termination Style  1.8 VAC  20ms  Socketable  Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	4.8 VAC
Release Time 20ms  Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	1.8 VAC
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

### MY4 AC6 (S) Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MY4 AC6 (S) Payment Methods



















## MY4 AC6 (S) Shipping Methods













If you have any question about MY4 AC6 (S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com