



MY4-DC12-EL Information

Heisener.com

Part Number MY4-DC12-EL

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 3A 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MY4-DC12-EL Specifications

Manufacturer Part Number MY4-DC12-EL Manufacturer Omron Automation and Safety Category Relays Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In		
Category Relays Power Relays, Over 2 Amps Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Manufacturer Part Number	MY4-DC12-EL
Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Purpose MY MY General Purpose General Purpose MY A Seneral Purpose 20mc Any	Manufacturer	Omron Automation and Safety
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Category	Relays
SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 75mB 1.2 VDC Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 20ms Release Time 20ms Release Time 20ms Features Features Features Features Plug In	Package	-
Coil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Series	MY
Coil Current Coil Voltage 12VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Coil Current	75mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style	Coil Voltage	12VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 7 Turn Off Voltage (Min) 9.6 VDC 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Contact Rating (Current)	3A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style 1.2 VDC 20ms Socketable Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	9.6 VDC
Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	1.2 VDC
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	-
·	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

MY4-DC12-EL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MY4-DC12-EL Payment Methods





















MY4-DC12-EL Shipping Methods













If you have any question about MY4-DC12-EL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com