



## **MY4I5N DC48 Information**

Heisener.com

Part Number MY4I5N DC48

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 4PDT 3A 48V

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MY4I5N DC48 Specifications**

Manufacturer Part NumberMY415N DC48ManufacturerOmron Automation and SafetyCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current18.5mACoil Voltage48VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)4.8 VDCOperate Time20msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In	•	
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         MY           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         18.5mA           Coil Voltage         48VDC           Contact Form         4PDT (4 Form C)           Contact Rating (Current)         3A           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         38.4 VDC           Operate Time         20ms           Release Time         20ms           Features         LED Indicator, Test Button           Mounting Type         Socketable	Manufacturer Part Number	MY4I5N DC48
Package Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 18.5mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type	Manufacturer	Omron Automation and Safety
Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 18.5mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable	Category	Relays
Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 18.5mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 20ms Release Time LED Indicator, Test Button Mounting Type Socketable		Power Relays, Over 2 Amps
Relay Type Coil Type Non Latching Coil Current 18.5mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 20ms Release Time LED Indicator, Test Button Mounting Type	Package	-
Coil TypeNon LatchingCoil Current18.5mACoil Voltage48VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)4.8 VDCOperate Time20msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketable	Series	MY
Coil Current Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 20ms Release Time LED Indicator, Test Button Mounting Type Socketable	Relay Type	General Purpose
Coil Voltage 48VDC  Contact Form 4PDT (4 Form C)  Contact Rating (Current) 3A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 38.4 VDC  Turn Off Voltage (Min) 4.8 VDC  Operate Time 20ms  Release Time 20ms  Features LED Indicator, Test Button  Mounting Type Socketable	Coil Type	Non Latching
Contact Form 4PDT (4 Form C)  Contact Rating (Current) 3A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 38.4 VDC  Turn Off Voltage (Min) 4.8 VDC  Operate Time 20ms  Release Time 20ms  Features LED Indicator, Test Button  Mounting Type Socketable	Coil Current	18.5mA
Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  38.4 VDC  Turn Off Voltage (Min)  4.8 VDC  Operate Time  20ms  Release Time  20ms  Features  LED Indicator, Test Button  Mounting Type  Socketable	Coil Voltage	48VDC
Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 38.4 VDC  Turn Off Voltage (Min) 4.8 VDC  Operate Time 20ms  Release Time 20ms  Features LED Indicator, Test Button  Mounting Type Socketable	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  4.8 VDC  Operate Time  20ms  Release Time  20ms  Features  LED Indicator, Test Button  Mounting Type  Socketable	Contact Rating (Current)	3A
Turn Off Voltage (Min)  Operate Time  20ms  Release Time  20ms  Features  LED Indicator, Test Button  Mounting Type  Socketable	Switching Voltage	250VAC, 125VDC - Max
Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable	Turn On Voltage (Max)	38.4 VDC
Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable	Turn Off Voltage (Min)	4.8 VDC
Features LED Indicator, Test Button  Mounting Type Socketable	Operate Time	20ms
Mounting Type Socketable	Release Time	20ms
	Features	LED Indicator, Test Button
Termination Style Plug In	Mounting Type	Socketable
	Termination Style	Plug In
Report errors?		Report errors?

#### **MY4I5N DC48 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **MY4I5N DC48 Payment Methods**





















## **MY4I5N DC48 Shipping Methods**













If you have any question about MY4I5N DC48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com