



Heisener.com

MY4N-AC110/120-EL Information

Part Number MY4N-AC110/120-EL

Manufacturer Omron Automation and Safety

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 3A 120V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MY4N-AC110/120-EL Specifications

Manufacturer Part Number My4N-AC110/120-EL Manufacturer Omron Automation and Safety Relays Power Relays, Over 2 Amps Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 8.4mA Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Mounting Type Socketable Plug In		
Category Relays Power Relays, Over 2 Amps Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 8.4mA Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 20ms Release Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style	Manufacturer Part Number	MY4N-AC110/120-EL
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.4mACoil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.4mACoil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Category	Relays
SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.4mACoil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 8.4mA Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current8.4mACoil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Series	MY
Coil Current Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Current	8.4mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Voltage	120VAC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 70 Voltage (Min) 60 VAC 70 Operate Time 70 Coms 70 Release Time 70 Coms 70 Coms 70 Coms 80 VAC 10 Coms 10 Coms 10 Coms 11 Coms 12 Coms 12 Coms 13 Coms 14 Coms 15 Coms 16 Coms 17 Coms 18	Contact Rating (Current)	3A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Turn On Voltage (Max)	96 VAC
Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	36 VAC
Features LED Indicator Mounting Type Socketable Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	LED Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
Report errors:		Report errors?

MY4N-AC110/120-EL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MY4N-AC110/120-EL Payment Methods



















MY4N-AC110/120-EL Shipping Methods













If you have any question about MY4N-AC110/120-EL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com