



MY4N-D2 DC125 Information

Heisener.com

Part Number MY4N-D2 DC125

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 3A 125V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MY4N-D2 DC125 Specifications

Manufacturer Part Number MY4N-D2 DC125 Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 7.2mA Coil Voltage 125 VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250 VAC, 125 VDC - Max Turn On Voltage (Max) 100 VDC Turn Off Voltage (Min) 12.5 VDC Operate Time 20ms Release Time 20ms Features Diode, LED Indicator Mounting Type Socketable Termination Style Plug In		
Category Relays Power Relays, Over 2 Amps Package Power Relays, Over 2 Amps Package Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 7.2mA Coil Voltage 125 VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125 VDC - Max Turn On Voltage (Max) 100 VDC Turn Off Voltage (Min) 12.5 VDC Operate Time 20ms Release Time 20ms Features Diode, LED Indicator Mounting Type Socketable Termination Style	Manufacturer Part Number	MY4N-D2 DC125
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current7.2mACoil Voltage125VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)100 VDCTurn Off Voltage (Min)12.5 VDCOperate Time20msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current7.2mACoil Voltage125VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)100 VDCTurn Off Voltage (Min)12.5 VDCOperate Time20msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Category	Relays
SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current7.2mACoil Voltage125 VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250 VAC, 125 VDC - MaxTurn On Voltage (Max)100 VDCTurn Off Voltage (Min)12.5 VDCOperate Time20msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 7.2mA Coil Voltage 125VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 100 VDC Turn Off Voltage (Min) 12.5 VDC Operate Time 20ms Release Time 20ms Release Time 20ms Features Diode, LED Indicator Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current7.2mACoil Voltage125VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)100 VDCTurn Off Voltage (Min)12.5 VDCOperate Time20msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Series	MY
Coil Current Coil Voltage 125VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 100 VDC Turn Off Voltage (Min) 12.5 VDC Operate Time 20ms Release Time 20ms Features Diode, LED Indicator Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage 125VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 100 VDC Turn Off Voltage (Min) 12.5 VDC Operate Time 20ms Release Time 20ms Features Diode, LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 100 VDC Turn Off Voltage (Min) 12.5 VDC Operate Time 20ms Release Time 20ms Features Diode, LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Current	7.2mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 100 VDC Turn Off Voltage (Min) 12.5 VDC Operate Time 20ms Release Time 20ms Features Diode, LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Voltage	125VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 100 VDC Turn Off Voltage (Min) 12.5 VDC Operate Time 20ms Release Time 20ms Features Diode, LED Indicator Mounting Type Socketable Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 100 VDC Turn Off Voltage (Min) 12.5 VDC Operate Time 20ms Release Time 20ms Features Diode, LED Indicator Mounting Type Socketable Termination Style Plug In	Contact Rating (Current)	3A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Diode, LED Indicator Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time20msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Turn On Voltage (Max)	100 VDC
Release Time 20ms Features Diode, LED Indicator Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	12.5 VDC
Features Diode, LED Indicator Mounting Type Socketable Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	Diode, LED Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

MY4N-D2 DC125 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MY4N-D2 DC125 Payment Methods



















MY4N-D2 DC125 Shipping Methods













If you have any question about MY4N-D2 DC125, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com