



## MY4N1 DC12 (S) Information

Heisener.com

Part Number MY4N1 DC12 (S)

Manufacturer Omron Automation and Safety

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 4PDT 3A 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MY4N1 DC12 (S) Specifications

Manufacturer Part Number         MY4N1 DC12 (S)           Manufacturer         Omron Automation and Safety           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         MY           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         75mA           Coil Voltage         12VDC           Contact Form         4PDT (4 Form C)           Contact Rating (Current)         3A           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         9.6 VDC           Turn Off Voltage (Min)         1.2 VDC           Operate Time         20ms           Release Time         20ms           Features         LED Indicator, Reverse Coil Polarity           Mounting Type         Socketable           Termination Style         Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeaturesLED Indicator, Reverse Coil PolarityMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	MY4N1 DC12 (S)
Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features LED Indicator, Reverse Coil Polarity Mounting Type Socketable Termination Style	Manufacturer	Omron Automation and Safety
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeaturesLED Indicator, Reverse Coil PolarityMounting TypeSocketableTermination StylePlug In	Category	Relays
SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeaturesLED Indicator, Reverse Coil PolarityMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 75mA  Coil Voltage 12VDC  Contact Form 4PDT (4 Form C)  Contact Rating (Current) 3A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 20ms  Release Time 20ms  Release Time LED Indicator, Reverse Coil Polarity  Mounting Type Socketable  Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeaturesLED Indicator, Reverse Coil PolarityMounting TypeSocketableTermination StylePlug In	Series	MY
Coil Current Coil Voltage 12VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features LED Indicator, Reverse Coil Polarity Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features LED Indicator, Reverse Coil Polarity Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C)  Contact Rating (Current) 3A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 20ms  Release Time 20ms  Features LED Indicator, Reverse Coil Polarity  Mounting Type Socketable  Termination Style Plug In	Coil Current	75mA
Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  9.6 VDC  Turn Off Voltage (Min)  1.2 VDC  Operate Time  20ms  Release Time  20ms  Features  LED Indicator, Reverse Coil Polarity  Mounting Type  Socketable  Termination Style	Coil Voltage	12VDC
Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 20ms  Release Time 20ms  Features LED Indicator, Reverse Coil Polarity  Mounting Type Socketable  Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max)  9.6 VDC  Turn Off Voltage (Min)  1.2 VDC  Operate Time  20ms  Release Time  20ms  Features  LED Indicator, Reverse Coil Polarity  Mounting Type  Socketable  Termination Style  Plug In	Contact Rating (Current)	3A
Turn Off Voltage (Min)  Operate Time  20ms  Release Time  20ms  LED Indicator, Reverse Coil Polarity  Mounting Type  Socketable  Termination Style  Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 20ms Release Time 20ms Features LED Indicator, Reverse Coil Polarity Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	9.6 VDC
Release Time 20ms  Features LED Indicator, Reverse Coil Polarity  Mounting Type Socketable  Termination Style Plug In	Turn Off Voltage (Min)	1.2 VDC
Features LED Indicator, Reverse Coil Polarity  Mounting Type Socketable  Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	LED Indicator, Reverse Coil Polarity
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

## MY4N1 DC12 (S) Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MY4N1 DC12 (S) Payment Methods



















## MY4N1 DC12 (S) Shipping Methods













If you have any question about MY4N1 DC12 (S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com