



MY4Z AC220/240 (S) Information

Heisener.com

Part Number MY4Z AC220/240 (S)

Manufacturer Omron Automation and Safety

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 3A 240V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MY4Z AC220/240 (S) Specifications

| Manufacturer Part Number MY4Z AC220/240 (\$) Manufacturer Omron Automation and Safety Category Relays Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 4.2mA Coil Voltage 240VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In | | |
|--|--------------------------|-----------------------------|
| CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.2mACoil Voltage240VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In | Manufacturer Part Number | MY4Z AC220/240 (S) |
| Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.2mACoil Voltage240VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In | Manufacturer | Omron Automation and Safety |
| Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 4.2mA Coil Voltage 240VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In | Category | Relays |
| SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.2mACoil Voltage240VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In | | Power Relays, Over 2 Amps |
| Relay Type General Purpose Coil Type Non Latching Coil Current 4.2mA Coil Voltage 240VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In | Package | - |
| Coil TypeNon LatchingCoil Current4.2mACoil Voltage240VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In | Series | MY |
| Coil Current Coil Voltage 240VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In | Relay Type | General Purpose |
| Coil Voltage 240VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In | Coil Type | Non Latching |
| Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In | Coil Current | 4.2mA |
| Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In | Coil Voltage | 240VAC |
| Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In | Contact Form | 4PDT (4 Form C) |
| Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style 192 VAC Plug In | Contact Rating (Current) | 3A |
| Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In | Switching Voltage | 250VAC, 125VDC - Max |
| Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In | Turn On Voltage (Max) | 192 VAC |
| Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In | Turn Off Voltage (Min) | 72 VAC |
| Features - Mounting Type Socketable Termination Style Plug In | Operate Time | 20ms |
| Mounting Type Socketable Termination Style Plug In | Release Time | 20ms |
| Termination Style Plug In | Features | - |
| | Mounting Type | Socketable |
| Report errors? | Termination Style | Plug In |
| | | Report errors? |

MY4Z AC220/240 (S) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MY4Z AC220/240 (S) Payment Methods



















MY4Z AC220/240 (S) Shipping Methods













If you have any question about MY4Z AC220/240 (S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com