



MY4ZIN AC12 (S) Information

Heisener.com

Part Number MY4ZIN AC12 (S)

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 3A 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MY4ZIN AC12 (S) Specifications

Manufacturer Part NumberMY4ZIN AC12 (S)ManufacturerOmron Automation and SafetyCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current91 mACoil Voltage12 VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250 VAC, 125 VDC - MaxTurn On Voltage (Max)9.6 VACTurn Off Voltage (Min)3.6 VACOperate Time20msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketable		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current91mACoil Voltage12VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VACTurn Off Voltage (Min)3.6 VACOperate Time20msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketable	Manufacturer Part Number	MY4ZIN AC12 (S)
Package Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 91mA Coil Voltage 12VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable	Manufacturer	Omron Automation and Safety
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current91mACoil Voltage12VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VACTurn Off Voltage (Min)3.6 VACOperate Time20msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketable	Category	Relays
SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current91mACoil Voltage12VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VACTurn Off Voltage (Min)3.6 VACOperate Time20msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketable		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 91mA Coil Voltage 12VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 20ms Release Time 20ms Release Time LED Indicator, Test Button Mounting Type Socketable	Package	-
Coil Type Non Latching Coil Current 91mA Coil Voltage 12VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 20ms Release Time 20ms Release Time LED Indicator, Test Button Mounting Type Socketable	Series	MY
Coil Current 91mA Coil Voltage 12VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 20ms Release Time 20ms Release Time LED Indicator, Test Button Mounting Type Socketable	Relay Type	General Purpose
Coil Voltage 12VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable	Coil Current	91mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable	Coil Voltage	12VAC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 9.6 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable	Contact Rating (Current)	3A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable	Switching Voltage	250VAC, 125VDC - Max
Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable	Turn On Voltage (Max)	9.6 VAC
Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable	Turn Off Voltage (Min)	3.6 VAC
Features LED Indicator, Test Button Mounting Type Socketable	Operate Time	20ms
Mounting Type Socketable	Release Time	20ms
	Features	LED Indicator, Test Button
	Mounting Type	Socketable
Termination Style Plug In	Termination Style	Plug In
Report errors?		Report errors?

MY4ZIN AC12 (S) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MY4ZIN AC12 (S) Payment Methods



















MY4ZIN AC12 (S) Shipping Methods













If you have any question about MY4ZIN AC12 (S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com