

Heisener.com

# **MY4ZIN AC220/240 (S)**

### MY4ZIN AC220/240 (S) Information

Part Number MY4ZIN AC220/240 (S)

Manufacturer Omron Automation and Safety

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 4PDT 3A 240V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### MY4ZIN AC220/240 (S) Specifications

Manufacturer Part Number         MY4ZIN AC220/240 (S)           Manufacturer         Omron Automation and Safety           Category         Relays           Package         -           Series         MY           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         4.2mA           Coil Voltage         240VAC           Contact Form         4PDT (4 Form C)           Contact Rating (Current)         3A           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         192 VAC           Turn Off Voltage (Min)         72 VAC           Operate Time         20ms           Release Time         20ms           Features         LED Indicator, Test Button           Mounting Type         Socketable           Termination Style         Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.2mACoil Voltage240VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	MY4ZIN AC220/240 (S)
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.2mACoil Voltage240VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.2mACoil Voltage240VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In	Category	Relays
SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.2mACoil Voltage240VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 4.2mA Coil Voltage 240VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Release Time LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current4.2mACoil Voltage240VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In	Series	MY
Coil Current Coil Voltage 240VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage 240VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C)  Contact Rating (Current) 3A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 192 VAC  Turn Off Voltage (Min) 72 VAC  Operate Time 20ms  Release Time 20ms  Features LED Indicator, Test Button  Mounting Type Socketable  Termination Style Plug In	Coil Current	4.2mA
Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  192 VAC  Turn Off Voltage (Min)  72 VAC  Operate Time  20ms  Release Time  20ms  Features  LED Indicator, Test Button  Mounting Type  Socketable  Termination Style  Plug In	Coil Voltage	240VAC
Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 192 VAC  Turn Off Voltage (Min) 72 VAC  Operate Time 20ms  Release Time 20ms  Features LED Indicator, Test Button  Mounting Type Socketable  Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max)  192 VAC  Turn Off Voltage (Min)  72 VAC  Operate Time  20ms  Release Time  20ms  Features  LED Indicator, Test Button  Mounting Type  Socketable  Termination Style  Plug In	Contact Rating (Current)	3A
Turn Off Voltage (Min)  72 VAC  Operate Time  20ms  Release Time  20ms  LED Indicator, Test Button  Mounting Type  Socketable  Termination Style  Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 20ms  Release Time 20ms  Features LED Indicator, Test Button  Mounting Type Socketable  Termination Style Plug In	Turn On Voltage (Max)	192 VAC
Release Time 20ms  Features LED Indicator, Test Button  Mounting Type Socketable  Termination Style Plug In	Turn Off Voltage (Min)	72 VAC
Features LED Indicator, Test Button  Mounting Type Socketable  Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	LED Indicator, Test Button
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

### MY4ZIN AC220/240 (S) Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

#### MY4ZIN AC220/240 (S) Payment Methods



















## MY4ZIN AC220/240 (S) Shipping Methods













If you have any question about MY4ZIN AC220/240 (S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com