



MY4ZIN DC48 (S) Information

Heisener.com

Part Number MY4ZIN DC48 (S)

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 3A 48V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MY4ZIN DC48 (S) Specifications

Manufacturer Part Number MY4ZIN DC48 (S) Manufacturer Omron Automation and Safety Category Relays Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 18.8mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current18.8mACoil Voltage48VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)4.8 VDCOperate Time20msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	MY4ZIN DC48 (S)
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current18.8mACoil Voltage48VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)4.8 VDCOperate Time20msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current18.8mACoil Voltage48VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)4.8 VDCOperate Time20msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In	Category	Relays
SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current18.8mACoil Voltage48VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)4.8 VDCOperate Time20msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 18.8mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 20ms Release Time LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current18.8mACoil Voltage48VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)4.8 VDCOperate Time20msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In	Series	MY
Coil Current Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Coil Current	18.8mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Coil Voltage	48VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Contact Rating (Current)	3A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 20ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	38.4 VDC
Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	4.8 VDC
Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	LED Indicator, Test Button
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

MY4ZIN DC48 (S) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MY4ZIN DC48 (S) Payment Methods



















MY4ZIN DC48 (S) Shipping Methods













If you have any question about MY4ZIN DC48 (S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com