

MY4ZN DC12 (S)

MY4ZN DC12 (S) Information

For Reference Only		MY4ZN DC12 (S) Omron Automation and Safety Relays Power Relays, Over 2 Amps RELAY GEN PURPOSE 4PDT 3A 12V	
	Package	For the pricing/inventory/lead time, please contact	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MY4ZN DC12 (S) Specifications

ManufacturerOmron Automation and SafetyCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketable		
CategoryRelaysPackage-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Man)9.6 VDCTurn Off Voltage (Min)1.2 VDCStease Time20msRelase Time20msFeaturesLED IndicatorMonting TypeSocketableTermination StylePlug In	Manufacturer Part Number	MY4ZN DC12 (S)
PackagePackagePackageMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCQoreat Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeBug In	Category	Relays
SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Package	-
Coil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Series	MY
Coil Current75mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Times20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Coil Type	Non Latching
Contact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Coil Current	75mA
Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Coil Voltage	12VDC
Switching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Contact Rating (Current)	3A
Turn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Turn On Voltage (Max)	9.6 VDC
Release Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Turn Off Voltage (Min)	1.2 VDC
FeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Operate Time	20ms
Mounting TypeSocketableTermination StylePlug In	Release Time	20ms
Termination Style Plug In	Features	LED Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

MY4ZN DC12 (S) Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MY4ZN DC12 (S) Payment Methods



MY4ZN DC12 (S) Shipping Methods



If you have any question about MY4ZN DC12 (S), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com