



### **MYQ4ZN DC100/110 Information**

Heisener.com

Part Number MYQ4ZN DC100/110

Manufacturer Omron Automation and Safety

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GEN PURPOSE 4PDT 1A 110V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MYQ4ZN DC100/110 Specifications**

Manufacturer Part Number     MYQ4ZN DC100/110       Manufacturer     Omron Automation and Safety       Category     Relays       Package     -       Series     MY       Relay Type     General Purpose       Coil Type     Non Latching       Coil Current     9.1mA       Coil Voltage     110VDC       Contact Form     4PDT (4 Form C)       Contact Rating (Current)     1A       Switching Voltage     250VAC, 125VDC - Max       Turn On Voltage (Max)     88 VDC       Turn Off Voltage (Min)     11 VDC       Operate Time     20ms       Release Time     20ms       Features     LED Indicator, Sealed - Fully       Mounting Type     Socketable       Termination Style     Plug In		
CategoryRelaysPackage-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.1mACoil Voltage110VDCContact Form4PDT (4 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)11 VDCOperate Time20msRelease Time20msFeaturesLED Indicator, Sealed - FullyMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	MYQ4ZN DC100/110
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.1mACoil Voltage110VDCContact Form4PDT (4 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)11 VDCOperate Time20msRelease Time20msFeaturesLED Indicator, Sealed - FullyMounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.1 mACoil Voltage110 VDCContact Form4PDT (4 Form C)Contact Rating (Current)1ASwitching Voltage250 VAC, 125 VDC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)11 VDCOperate Time20msRelease Time20msFeaturesLED Indicator, Sealed - FullyMounting TypeSocketableTermination StylePlug In	Category	Relays
SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.1mACoil Voltage110VDCContact Form4PDT (4 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)11 VDCOperate Time20msRelease Time20msFeaturesLED Indicator, Sealed - FullyMounting TypeSocketableTermination StylePlug In		Signal Relays, Up to 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 9.1mA Coil Voltage 110VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 11 VDC Operate Time 20ms Release Time 20ms Features LED Indicator, Sealed - Fully Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current9.1mACoil Voltage110VDCContact Form4PDT (4 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)11 VDCOperate Time20msRelease Time20msFeaturesLED Indicator, Sealed - FullyMounting TypeSocketableTermination StylePlug In	Series	MY
Coil Current Coil Voltage 110VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 11 VDC Operate Time 20ms Release Time 20ms Features LED Indicator, Sealed - Fully Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage 110VDC  Contact Form 4PDT (4 Form C)  Contact Rating (Current) 1A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 88 VDC  Turn Off Voltage (Min) 11 VDC  Operate Time 20ms  Release Time 20ms  Features LED Indicator, Sealed - Fully  Mounting Type Socketable  Termination Style Plug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C)  Contact Rating (Current) 1A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 88 VDC  Turn Off Voltage (Min) 11 VDC  Operate Time 20ms  Release Time 20ms  Release Time LED Indicator, Sealed - Fully  Mounting Type Socketable  Termination Style Plug In	Coil Current	9.1mA
Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  88 VDC  Turn Off Voltage (Min)  11 VDC  Operate Time  20ms  Release Time  20ms  Features  LED Indicator, Sealed - Fully  Mounting Type  Socketable  Termination Style  Plug In	Coil Voltage	110VDC
Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 88 VDC  Turn Off Voltage (Min) 11 VDC  Operate Time 20ms  Release Time 20ms  Features LED Indicator, Sealed - Fully  Mounting Type Socketable  Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  20ms  Release Time  20ms  Features  LED Indicator, Sealed - Fully  Mounting Type  Socketable  Termination Style  Plug In	Contact Rating (Current)	1A
Turn Off Voltage (Min)  Operate Time  20ms  Release Time  20ms  Features  LED Indicator, Sealed - Fully  Mounting Type  Socketable  Termination Style  Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time20msRelease Time20msFeaturesLED Indicator, Sealed - FullyMounting TypeSocketableTermination StylePlug In	Turn On Voltage (Max)	88 VDC
Release Time 20ms  Features LED Indicator, Sealed - Fully  Mounting Type Socketable  Termination Style Plug In	Turn Off Voltage (Min)	11 VDC
Features  LED Indicator, Sealed - Fully  Mounting Type  Socketable  Termination Style  Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	LED Indicator, Sealed - Fully
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

### MYQ4ZN DC100/110 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MYQ4ZN DC100/110 Payment Methods



















# **MYQ4ZN DC100/110 Shipping Methods**













If you have any question about MYQ4ZN DC100/110, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com