

**N2516-6002-UB Information**


For Reference Only

**Part Number** [N2516-6002-UB](#)  
**Manufacturer** 3M  
**Category** Connectors, Interconnects  
[Rectangular Connectors - Headers, Male Pins](#)  
**Description** CONN HEADER 16POS STR GOLD T/H  
**Package** -  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)



[Request a Quote](#)

**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**N2516-6002-UB Specifications**

|                            |  |
|----------------------------|--|
| Manufacturer Part Number   | <a href="#">N2516-6002-UB</a>  |
| Manufacturer               | 3M   |
| Category                   | Connectors, Interconnects<br><a href="#">Rectangular Connectors - Headers, Male Pins</a> |
| Package                    | -  |
| Series                     | 2500   |
| Connector Type             | Header   |
| Contact Type               | Male Pin   |
| Pitch - Mating             | 0.100" (2.54mm)  |
| Style                      | Board to Board or Cable  |
| Shrouding                  | Shrouded - 4 Wall  |
| Number of Positions        | 16   |
| Number of Positions Loaded | All  |
| Number of Rows             | 2  |
| Row Spacing - Mating       | 0.100" (2.54mm)  |
| Mounting Type              | Through Hole   |
| Termination                | Solder   |
| Fastening Type             | Push-Pull  |
| Contact Length - Mating    | 0.243" (6.17mm)  |
| Contact Length - Post      | 0.112" (2.84mm)  |
| Overall Contact Length     | -  |
| Insulation Height          | 0.390" (9.91mm)  |
| Contact Shape              | Square   |
| Contact Finish - Mating    | Gold   |

|                                   |   |
|-----------------------------------|---|
| Contact Finish Thickness - Mating | 30µin (0.76µm)  |
| Contact Finish - Post             | Tin-Lead  |
| Contact Material                  | Copper Alloy  |
| Insulation Material               | Polycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass Filled |
| Features                          | Keying Slot   |
| Operating Temperature             | -55°C ~ 105°C   |
| Ingress Protection                | -   |
| Material Flammability Rating      | UL94 V-0  |
| Insulation Color                  | Black   |

[Report errors?](#)

## N2516-6002-UB Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## N2516-6002-UB Payment Methods



## N2516-6002-UB Shipping Methods



If you have any question about N2516-6002-UB, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)