

N25Q032A13ESE40F TR

N25Q032A13ESE40F TR Information



For Reference Only

Part NumberN25Q032A13ESE40F TRManufacturerMicron Technology Inc.CategoryIntegrated Circuits (ICs)

Memory

DescriptionIC FLASH 32MBIT 108MHZ 8SO**Package**8-SOIC (0.209", 5.30mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









N25Q032A13ESE40F TR Specifications

Manufacturer Part Number N25Q032A13ESE40F TR Manufacturer Micron Technology Inc. Category Integrated Circuits (ICs) Memory Memory Package 8-SOIC (0.209", 5.30mm Width) Series - Memory Type Non-Volatile Memory Format FLASH Technology FLASH - NOR Memory Size 32Mb (8M x 4) Memory Interface SPI Clock Frequency 108MHz Write Cycle Time - Word, Page 8ms, 5ms Access Time - Voltage - Supply 2.7 V ~ 3.6 V Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width)		
Category Integrated Circuits (ICs) Memory Package 8-SOIC (0.209", 5.30mm Width) Series - Memory Type Non-Volatile Memory Format FLASH Technology FLASH - NOR Memory Size 32Mb (8M x 4) Memory Interface SPI Clock Frequency 108MHz Write Cycle Time - Word, Page 8ms, 5ms Access Time - Voltage - Supply 2.7 V ~ 3.6 V Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width)	Manufacturer Part Number	N25Q032A13ESE40F TR
Memory Package 8-SOIC (0.209", 5.30mm Width) Series - Memory Type Non-Volatile Memory Format FLASH Technology FLASH - NOR Memory Size 32Mb (8M x 4) Memory Interface SPI Clock Frequency 108MHz Write Cycle Time - Word, Page 8ms, 5ms Access Time - Voltage - Supply 2.7 V ~ 3.6 V Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width)	Manufacturer	Micron Technology Inc.
Package 8-SOIC (0.209", 5.30mm Width) Series	Category	Integrated Circuits (ICs)
Series - Memory Type Non-Volatile Memory Format FLASH Technology FLASH - NOR Memory Size 32Mb (8M x 4) Memory Interface SPI Clock Frequency 108MHz Write Cycle Time - Word, Page 8ms, 5ms Access Time - Voltage - Supply 2.7 V ~ 3.6 V Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width)		Memory
Memory TypeNon-VolatileMemory FormatFLASHTechnologyFLASH - NORMemory Size32Mb (8M x 4)Memory InterfaceSPIClock Frequency108MHzWrite Cycle Time - Word, Page8ms, 5msAccess Time-Voltage - Supply2.7 V ~ 3.6 VOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / Case8-SOIC (0.209", 5.30mm Width)	Package	8-SOIC (0.209", 5.30mm Width)
Memory FormatFLASHTechnologyFLASH - NORMemory Size32Mb (8M x 4)Memory InterfaceSPIClock Frequency108MHzWrite Cycle Time - Word, Page8ms, 5msAccess Time-Voltage - Supply2.7 V ~ 3.6 VOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / Case8-SOIC (0.209", 5.30mm Width)	Series	-
Technology FLASH - NOR Memory Size 32Mb (8M x 4) Memory Interface SPI Clock Frequency 108MHz Write Cycle Time - Word, Page 8ms, 5ms Access Time - Voltage - Supply 2.7 V ~ 3.6 V Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width)	Memory Type	Non-Volatile
Memory Size32Mb (8M x 4)Memory InterfaceSPIClock Frequency108MHzWrite Cycle Time - Word, Page8ms, 5msAccess Time-Voltage - Supply2.7 V ~ 3.6 VOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / Case8-SOIC (0.209", 5.30mm Width)	Memory Format	FLASH
Memory InterfaceSPIClock Frequency108MHzWrite Cycle Time - Word, Page8ms, 5msAccess Time-Voltage - Supply2.7 V ~ 3.6 VOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / Case8-SOIC (0.209", 5.30mm Width)	Technology	FLASH - NOR
Clock Frequency Write Cycle Time - Word, Page 8ms, 5ms Access Time - Voltage - Supply 2.7 V ~ 3.6 V Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width)	Memory Size	32Mb (8M x 4)
Write Cycle Time - Word, Page Access Time - Voltage - Supply 2.7 V ~ 3.6 V Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width)	Memory Interface	SPI
Access Time - Voltage - Supply 2.7 V \sim 3.6 V Operating Temperature -40°C \sim 85°C (TA) Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width)	Clock Frequency	108MHz
Voltage - Supply $2.7 \text{ V} \sim 3.6 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C (TA)}$ Mounting Type Surface Mount Package / Case $8\text{-SOIC (0.209", 5.30mm Width)}$	Write Cycle Time - Word, Page	8ms, 5ms
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C} \text{ (TA)}$ Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width)	Access Time	-
Mounting Type Surface Mount Package / Case 8-SOIC (0.209", 5.30mm Width)	Voltage - Supply	2.7 V ~ 3.6 V
Package / Case 8-SOIC (0.209", 5.30mm Width)	Operating Temperature	-40°C ~ 85°C (TA)
	Mounting Type	Surface Mount
0.0000	Package / Case	8-SOIC (0.209", 5.30mm Width)
Supplier Device Package 8-SOP2	Supplier Device Package	8-SOP2
Report errors?		Report errors?

N25Q032A13ESE40F TR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

N25Q032A13ESE40F TR Payment Methods



















N25Q032A13ESE40F TR Shipping Methods













If you have any question about N25Q032A13ESE40F TR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com