

NBPDANN001PGUNV

NBPDANN001PGUNV Information



For Reference Only

Part Number NBPDANN001PGUNV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

DescriptionBRD MNT PRESSURE SENSORS**Package**4-DIP (0.453", 11.50mm), Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NBPDANN001PGUNV Specifications

| Manufacturer Part NumberNBPDANN001PGUNVManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage4-DIP (0.453", 11.50mm), Top PortSeriesNBPPressure TypeVented GaugeOperating Pressure1 PSI (6.89 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 32.5 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.75" (1.91mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure10 PSI (68.95 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package-Report errors? | | |
|--|--------------------------|---|
| CategorySensors, TransducersPackage4-DIP (0.453", 11.50mm), Top PortSeriesNBPPressure TypeVented GaugeOperating Pressure1 PSI (6.89 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 32.5 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.75" (1.91mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure10 PSI (68.95 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package- | Manufacturer Part Number | NBPDANN001PGUNV |
| Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Vented Gauge Operating Pressure 1 PSI (6.89 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 32.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.75" (1.91mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Manufacturer | Honeywell Sensing and Productivity Solutions |
| Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Vented Gauge Operating Pressure 1 PSI (6.89 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 32.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.75" (1.91mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Category | Sensors, Transducers |
| SeriesNBPPressure TypeVented GaugeOperating Pressure1 PSI (6.89 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 32.5 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.75" (1.91mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure10 PSI (68.95 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package- | | Pressure Sensors, Transducers |
| Pressure TypeVented GaugeOperating Pressure1 PSI (6.89 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 32.5 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.75" (1.91mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure10 PSI (68.95 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package- | Package | 4-DIP (0.453", 11.50mm), Top Port |
| Operating Pressure 1 PSI (6.89 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 32.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.75" (1.91mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Series | NBP |
| Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 32.5 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port SizeMale - 0.75 " (1.91mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure $10 \text{ PSI} (68.95 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-DIP} (0.453", 11.50\text{mm}), \text{Top Port}$ Supplier Device Package- | Pressure Type | Vented Gauge |
| Output $0 \text{ mV} \sim 32.5 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size $\text{Male} - 0.75'' (1.91 \text{mm}) \text{ Tube}$ Port Style Barbed Features - Termination Style PC Pin Maximum Pressure $10 \text{ PSI } (68.95 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-DIP } (0.453'', 11.50 \text{mm}), \text{Top Port}$ Supplier Device Package $-$ | Operating Pressure | 1 PSI (6.89 kPa) |
| Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port SizeMale - 0.75 " (1.91mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure $10 \text{ PSI } (68.95 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-DIP } (0.453\text{"}, 11.50 \text{mm}), \text{Top Port}$ Supplier Device Package- | Output Type | Wheatstone Bridge |
| Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.75" (1.91mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package | Output | $0 \text{ mV} \sim 32.5 \text{ mV} (5\text{V})$ |
| Port Size Male - 0.75" (1.91mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Accuracy | ±0.25% |
| Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Voltage - Supply | 1.8 V ~ 12 V |
| Features - Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Port Size | Male - 0.75" (1.91mm) Tube |
| Termination Style PC Pin Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Port Style | Barbed |
| Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Features | - |
| Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Termination Style | PC Pin |
| Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Maximum Pressure | 10 PSI (68.95 kPa) |
| Supplier Device Package - | Operating Temperature | -40°C ~ 125°C |
| | Package / Case | 4-DIP (0.453", 11.50mm), Top Port |
| Report errors? | Supplier Device Package | - |
| | | Report errors? |

NBPDANN001PGUNV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NBPDANN001PGUNV Payment Methods



















NBPDANN001PGUNV Shipping Methods













If you have any question about NBPDANN001PGUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com