

NBPDANN150PAUNV

NBPDANN150PAUNV Information



For Reference Only

Part Number NBPDANN150PAUNV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR 150 PSIA UNAMPLIFIED DIP

Package 4-DIP (0.453", 11.50mm), Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NBPDANN150PAUNV Specifications

Manufacturer Part Number NBPDANN150PAUNV Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Absolute Operating Pressure 150 PSI (1034.21 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 130 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.08" (1.91mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 240 PSI (1654.74 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -		
Category Sensors, Transducers Pressure Sensors, Transducers Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Absolute Operating Pressure 150 PSI (1034.21 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 130 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.08" (1.91mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 240 PSI (1654.74 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Manufacturer Part Number	NBPDANN150PAUNV
Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Absolute Operating Pressure 150 PSI (1034.21 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 130 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.08" (1.91mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 240 PSI (1654.74 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Manufacturer	Honeywell Sensing and Productivity Solutions
Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Absolute Operating Pressure 150 PSI (1034.21 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 130 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.08" (1.91mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 240 PSI (1654.74 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Category	Sensors, Transducers
SeriesNBPPressure TypeAbsoluteOperating Pressure150 PSI (1034.21 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 130 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.08" (1.91mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure240 PSI (1654.74 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeAbsoluteOperating Pressure150 PSI (1034.21 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 130 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.08" (1.91mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure240 PSI (1654.74 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package-	Package	4-DIP (0.453", 11.50mm), Top Port
Operating Pressure Output Type Wheatstone Bridge Output OmV ~ 130 mV (5V) Accuracy ±0.25% Voltage - Supply Port Size Male - 0.08" (1.91mm) Tube Port Style Barbed Features - Termination Style Maximum Pressure Operating Temperature -40°C ~ 125°C Package / Case Supplier Device Package 150 PSI (1034.21 kPa) Wheatstone Bridge Wheatstone Bridge Wheatstone Bridge Wheatstone Bridge 10.94 No	Series	NBP
Output TypeWheatstone BridgeOutput0 mV ~ 130 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.08" (1.91mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure240 PSI (1654.74 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package-	Pressure Type	Absolute
Output $0 \text{ mV} \sim 130 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size $Male - 0.08'' (1.91 \text{mm})$ Tube Port Style $Barbed$ Features - Termination Style $PC Pin$ Maximum Pressure $240 PSI (1654.74 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-DIP} (0.453'', 11.50 \text{mm})$, Top Port Supplier Device Package $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Operating Pressure	150 PSI (1034.21 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port SizeMale - 0.08 " (1.91mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure $240 \text{ PSI } (1654.74 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-DIP } (0.453\text{"}, 11.50\text{mm}), \text{Top Port}$ Supplier Device Package-	Output Type	Wheatstone Bridge
Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size $\text{Male - 0.08" (1.91 \text{mm}) Tube}$ Port Style Barbed Features $-$ Termination Style PC Pin Maximum Pressure $240 \text{ PSI (1654.74 kPa)}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4-\text{DIP (0.453", 11.50 \text{mm}), Top Port}$ Supplier Device Package $-$	Output	$0 \text{ mV} \sim 130 \text{ mV} (5\text{V})$
Port Size Male - 0.08" (1.91mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 240 PSI (1654.74 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Accuracy	±0.25%
Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 240 PSI (1654.74 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Voltage - Supply	1.8 V ~ 12 V
Features - Termination Style PC Pin Maximum Pressure 240 PSI (1654.74 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Port Size	Male - 0.08" (1.91mm) Tube
Termination Style PC Pin Maximum Pressure 240 PSI (1654.74 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Port Style	Barbed
Maximum Pressure 240 PSI (1654.74 kPa) Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Features	-
Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Termination Style	PC Pin
Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Maximum Pressure	240 PSI (1654.74 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	4-DIP (0.453", 11.50mm), Top Port
Report errors?	Supplier Device Package	-
The post straight		Report errors?

NBPDANN150PAUNV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NBPDANN150PAUNV Payment Methods



















NBPDANN150PAUNV Shipping Methods













If you have any question about NBPDANN150PAUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com