

NBPDANN400MGUNV

NBPDANN400MGUNV Information



For Reference Only

Part Number NBPDANN400MGUNV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

DescriptionBRD MNT PRESSURE SENSORS**Package**4-DIP (0.453", 11.50mm), Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NBPDANN400MGUNV Specifications

Manufacturer Part Number NBPDANN400MGUNV Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Pressure Sensors, Transducers Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Vented Gauge Operating Pressure 5.8 PSI (40 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 87 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.75" (1.91mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 26.11 PSI (180 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -			
Category Sensors, Transducers Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Vented Gauge Operating Pressure 5.8 PSI (40 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 87 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.75" (1.91mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 26.11 PSI (180 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Manufacturer Part Number	NBPDANN400MGUNV	
Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Vented Gauge Operating Pressure 5.8 PSI (40 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 87 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.75" (1.91mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 26.11 PSI (180 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Manufacturer	Honeywell Sensing and Productivity Solutions	
Package4-DIP (0.453", 11.50mm), Top PortSeriesNBPPressure TypeVented GaugeOperating Pressure5.8 PSI (40 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 87 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.75" (1.91mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure26.11 PSI (180 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package-	Category	Sensors, Transducers	
SeriesNBPPressure TypeVented GaugeOperating Pressure5.8 PSI (40 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 87 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.75" (1.91mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure26.11 PSI (180 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package-		Pressure Sensors, Transducers	
Pressure Type Vented Gauge Operating Pressure 5.8 PSI (40 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 87 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.75" (1.91mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 26.11 PSI (180 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package	Package	4-DIP (0.453", 11.50mm), Top Port	
Operating Pressure 5.8 PSI (40 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 87 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.75" (1.91mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 26.11 PSI (180 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package	Series	NBP	
Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 87 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port SizeMale - 0.75 " (1.91mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure $26.11 \text{ PSI } (180 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-DIP } (0.453\text{", } 11.50\text{mm}), \text{ Top Port}$ Supplier Device Package-	Pressure Type	Vented Gauge	
Output $0 \text{ mV} \sim 87 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size $Male - 0.75" (1.91 \text{mm}) \text{ Tube}$ Port Style $Barbed$ Features - Termination Style $PC Pin$ Maximum Pressure $26.11 PSI (180 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-DIP} (0.453", 11.50 \text{mm}), \text{Top Port}$ Supplier Device Package $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Operating Pressure	5.8 PSI (40 kPa)	
Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size $Male - 0.75" (1.91 \text{mm}) \text{ Tube}$ Port Style $Barbed$ Features $-$ Termination Style $PC Pin$ Maximum Pressure $26.11 PSI (180 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-DIP } (0.453", 11.50 \text{mm}), \text{ Top Port}$ Supplier Device Package $-$	Output Type	Wheatstone Bridge	
Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.75" (1.91mm) Tube Barbed Features - Termination Style PC Pin Maximum Pressure 26.11 PSI (180 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package	Output	0 mV ~ 87 mV (5V)	
Port Size Male - 0.75" (1.91mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 26.11 PSI (180 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Accuracy	±0.25%	
Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 26.11 PSI (180 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Voltage - Supply	1.8 V ~ 12 V	
Features - Termination Style PC Pin Maximum Pressure 26.11 PSI (180 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Port Size	Male - 0.75" (1.91mm) Tube	
Termination Style PC Pin Maximum Pressure 26.11 PSI (180 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Port Style	Barbed	
Maximum Pressure $26.11 \text{ PSI } (180 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-DIP } (0.453'', 11.50 \text{mm}), \text{Top Port}$ Supplier Device Package $-$	Features	-	
Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Termination Style	PC Pin	
Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Maximum Pressure	26.11 PSI (180 kPa)	
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C	
	Package / Case	4-DIP (0.453", 11.50mm), Top Port	
Report errors?	Supplier Device Package	-	
		Report error	s?

NBPDANN400MGUNV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NBPDANN400MGUNV Payment Methods



















NBPDANN400MGUNV Shipping Methods













If you have any question about NBPDANN400MGUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com