

### NBPDANS060PGUNV

#### **NBPDANS060PGUNV Information**



For Reference Only

Part Number NBPDANS060PGUNV

Manufacturer Honeywell Sensing and Productivity Solutions

**Category** Sensors, Transducers

Pressure Sensors, Transducers

**Description**BRD MNT PRESSURE SENSORS**Package**4-DIP (0.453", 11.50mm), Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **NBPDANS060PGUNV Specifications**

Manufacturer Part NumberNBPDANS060PGUNVManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage4-DIP (0.453", 11.50mm), Top PortSeriesNBPPressure TypeVented GaugeOperating Pressure60 PSI (413.69 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 105 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.75" (1.91mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure120 PSI (827.37 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package-Report errors?		
CategorySensors, TransducersPackage4-DIP (0.453", 11.50mm), Top PortSeriesNBPPressure TypeVented GaugeOperating Pressure60 PSI (413.69 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 105 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.75" (1.91mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure120 PSI (827.37 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package-	Manufacturer Part Number	NBPDANS060PGUNV
Package         4-DIP (0.453", 11.50mm), Top Port           Series         NBP           Pressure Type         Vented Gauge           Operating Pressure         60 PSI (413.69 kPa)           Output Type         Wheatstone Bridge           Output         0 mV ~ 105 mV (5V)           Accuracy         ±0.25%           Voltage - Supply         1.8 V ~ 12 V           Port Size         Male - 0.75" (1.91mm) Tube           Port Style         Barbed           Features         -           Termination Style         PC Pin           Maximum Pressure         120 PSI (827.37 kPa)           Operating Temperature         -40°C ~ 125°C           Package / Case         4-DIP (0.453", 11.50mm), Top Port           Supplier Device Package         -	Manufacturer	Honeywell Sensing and Productivity Solutions
Package         4-DIP (0.453", 11.50mm), Top Port           Series         NBP           Pressure Type         Vented Gauge           Operating Pressure         60 PSI (413.69 kPa)           Output Type         Wheatstone Bridge           Output         0 mV ~ 105 mV (5V)           Accuracy         ±0.25%           Voltage - Supply         1.8 V ~ 12 V           Port Size         Male - 0.75" (1.91mm) Tube           Port Style         Barbed           Features         -           Termination Style         PC Pin           Maximum Pressure         120 PSI (827.37 kPa)           Operating Temperature         -40°C ~ 125°C           Package / Case         4-DIP (0.453", 11.50mm), Top Port           Supplier Device Package         -	Category	Sensors, Transducers
SeriesNBPPressure TypeVented GaugeOperating Pressure60 PSI (413.69 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 105 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.75" (1.91mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure120 PSI (827.37 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure60 PSI (413.69 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 105 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.75" (1.91mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure120 PSI (827.37 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package-	Package	4-DIP (0.453", 11.50mm), Top Port
Operating Pressure 60 PSI (413.69 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.75" (1.91mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 120 PSI (827.37 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Series	NBP
Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 105 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port SizeMale - $0.75$ " $(1.91\text{mm})$ TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure $120 \text{ PSI } (827.37 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-DIP } (0.453\text{"}, 11.50\text{mm}), \text{Top Port}$ Supplier Device Package-	Pressure Type	Vented Gauge
Output $0 \text{ mV} \sim 105 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size $Male - 0.75" (1.91 \text{mm}) \text{ Tube}$ Port Style $Barbed$ Features - Termination Style $PC Pin$ Maximum Pressure $PC Pin$ Maximum Pressure $PC Pin$ Poperating Temperature $PC Pin$ Package / Case $PC Pin$ Package / Case $PC Pin$ Supplier Device Package $PC Pin$	Operating Pressure	60 PSI (413.69 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port SizeMale - $0.75$ " ( $1.91 \text{mm}$ ) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure $120 \text{ PSI } (827.37 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-DIP } (0.453\text{"}, 11.50 \text{mm}), \text{Top Port}$ Supplier Device Package-	Output Type	Wheatstone Bridge
Voltage - Supply  1.8 V ~ 12 V  Port Size  Male - 0.75" (1.91mm) Tube  Port Style  Barbed  Features  -  Termination Style  PC Pin  Maximum Pressure  120 PSI (827.37 kPa)  Operating Temperature  -40°C ~ 125°C  Package / Case  4-DIP (0.453", 11.50mm), Top Port  Supplier Device Package  -	Output	$0 \text{ mV} \sim 105 \text{ mV} (5\text{V})$
Port Size Male - 0.75" (1.91mm) Tube  Port Style Barbed  Features -  Termination Style PC Pin  Maximum Pressure 120 PSI (827.37 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case 4-DIP (0.453", 11.50mm), Top Port  Supplier Device Package -	Accuracy	±0.25%
Port Style Barbed  Features -  Termination Style PC Pin  Maximum Pressure 120 PSI (827.37 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case 4-DIP (0.453", 11.50mm), Top Port  Supplier Device Package -	Voltage - Supply	1.8 V ~ 12 V
Features - Termination Style PC Pin  Maximum Pressure 120 PSI (827.37 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case 4-DIP (0.453", 11.50mm), Top Port  Supplier Device Package -	Port Size	Male - 0.75" (1.91mm) Tube
Termination Style PC Pin  Maximum Pressure 120 PSI (827.37 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case 4-DIP (0.453", 11.50mm), Top Port  Supplier Device Package -	Port Style	Barbed
Maximum Pressure  120 PSI (827.37 kPa)  Operating Temperature  -40°C ~ 125°C  Package / Case  4-DIP (0.453", 11.50mm), Top Port  Supplier Device Package  -	Features	-
Operating Temperature -40°C ~ 125°C  Package / Case 4-DIP (0.453", 11.50mm), Top Port  Supplier Device Package -	Termination Style	PC Pin
Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Maximum Pressure	120 PSI (827.37 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	4-DIP (0.453", 11.50mm), Top Port
Report errors?	Supplier Device Package	-
		Report errors?

#### **NBPDANS060PGUNV Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **NBPDANS060PGUNV Payment Methods**



















# NBPDANS060PGUNV Shipping Methods













If you have any question about NBPDANS060PGUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com