

NBPDLNN060PGUNV

NBPDLNN060PGUNV Information



For Reference Only

Part Number NBPDLNN060PGUNV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

DescriptionSENSOR PRES 60PSI GAUG 12V DIP**Package**4-DIP (0.453", 11.50mm), Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NBPDLNN060PGUNV Specifications

Manufacturer Part NumberNBPDLNN060PGUNVManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage4-DIP (0.453", 11.50mm), Top PortSeriesNBPPressure TypeVented GaugeOperating Pressure60 PSI (413.69 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 105 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure240 PSI (1654.74 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top Port			
Category Sensors, Transducers Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Vented Gauge Operating Pressure 60 PSI (413.69 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 240 PSI (1654.74 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Manufacturer Part Number	NBPDLNN060PGUNV	
Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Vented Gauge Operating Pressure 60 PSI (413.69 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 240 PSI (1654.74 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions	
Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Vented Gauge Operating Pressure 60 PSI (413.69 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 240 PSI (1654.74 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Category	Sensors, Transducers	
SeriesNBPPressure TypeVented GaugeOperating Pressure60 PSI (413.69 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 105 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure240 PSI (1654.74 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package-		Pressure Sensors, Transducers	
Pressure Type Vented Gauge Operating Pressure 60 PSI (413.69 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 240 PSI (1654.74 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Package	4-DIP (0.453", 11.50mm), Top Port	
Operating Pressure 60 PSI (413.69 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 240 PSI (1654.74 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package	Series	NBP	
Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 105 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port SizeMale - 0.13 " (3.18mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure $240 \text{ PSI} (1654.74 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-DIP} (0.453\text{"}, 11.50\text{mm}), \text{Top Port}$ Supplier Device Package-	Pressure Type	Vented Gauge	
Output $0 \text{ mV} \sim 105 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port SizeMale - 0.13 " (3.18mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure $240 \text{ PSI} (1654.74 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-DIP} (0.453\text{"}, 11.50\text{mm}), \text{Top Port}$ Supplier Device Package-	Operating Pressure	60 PSI (413.69 kPa)	
Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size $Male - 0.13" (3.18 \text{mm}) \text{ Tube}$ Port Style $Barbless$ Features - Termination Style $PC Pin$ Maximum Pressure $240 \text{ PSI } (1654.74 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-DIP } (0.453", 11.50 \text{mm}), \text{Top Port}$ Supplier Device Package $-$	Output Type	Wheatstone Bridge	
Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 240 PSI (1654.74 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package	Output	$0 \text{ mV} \sim 105 \text{ mV} (5\text{V})$	
Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 240 PSI (1654.74 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Accuracy	±0.25%	
Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 240 PSI (1654.74 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Voltage - Supply	1.8 V ~ 12 V	
Features - Termination Style PC Pin Maximum Pressure 240 PSI (1654.74 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Port Size	Male - 0.13" (3.18mm) Tube	
Termination Style PC Pin Maximum Pressure 240 PSI (1654.74 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Port Style	Barbless	
	Features	-	
Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Termination Style	PC Pin	
Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Maximum Pressure	240 PSI (1654.74 kPa)	
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C	
	Package / Case	4-DIP (0.453", 11.50mm), Top Port	
D	Supplier Device Package	-	
Report errors?		Report error	s?

NBPDLNN060PGUNV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NBPDLNN060PGUNV Payment Methods



















NBPDLNN060PGUNV Shipping Methods













If you have any question about NBPDLNN060PGUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com