

NBPDLNS060MGUNV

NBPDLNS060MGUNV Information



For Reference Only

Part Number NBPDLNS060MGUNV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

DescriptionBRD MNT PRESSURE SENSORS**Package**4-DIP (0.453", 11.50mm), Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NBPDLNS060MGUNV Specifications

| Manufacturer Part Number NBPDLNS060MGUNV Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Vented Gauge Operating Pressure 0.87 PSI (6 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 28.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - Report errors? | | | |
|--|--------------------------|---|----------------|
| Category Sensors, Transducers Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Vented Gauge Operating Pressure 0.87 PSI (6 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 28.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Manufacturer Part Number | NBPDLNS060MGUNV | |
| Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Vented Gauge Operating Pressure 0.87 PSI (6 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 28.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Manufacturer | Honeywell Sensing and Productivity Solutions | |
| Package4-DIP (0.453", 11.50mm), Top PortSeriesNBPPressure TypeVented GaugeOperating Pressure0.87 PSI (6 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 28.5 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure12.33 PSI (85 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package- | Category | Sensors, Transducers | |
| SeriesNBPPressure TypeVented GaugeOperating Pressure0.87 PSI (6 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 28.5 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure12.33 PSI (85 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package- | | Pressure Sensors, Transducers | |
| Pressure Type Vented Gauge Operating Pressure 0.87 PSI (6 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 28.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package | Package | 4-DIP (0.453", 11.50mm), Top Port | |
| Operating Pressure Output Type Wheatstone Bridge Output OmV ~ 28.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Series | NBP | |
| Output Type Wheatstone Bridge Output 0 mV ~ 28.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Pressure Type | Vented Gauge | |
| Output $0 \text{ mV} \sim 28.5 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size $Male - 0.13'' (3.18 \text{mm})$ Tube Port Style $Barbless$ Features $-$ Termination Style $PC Pin$ Maximum Pressure $12.33 \text{ PSI } (85 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-DIP } (0.453'', 11.50 \text{mm})$, Top Port | Operating Pressure | 0.87 PSI (6 kPa) | |
| Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size $Male - 0.13'' (3.18 \text{mm}) \text{ Tube}$ Port Style $Barbless$ Features $-$ Termination Style $PC Pin$ Maximum Pressure $12.33 \text{ PSI (85 kPa)}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-DIP (0.453'', 11.50 \text{mm}), Top Port}$ Supplier Device Package $-$ | Output Type | Wheatstone Bridge | |
| Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package | Output | $0 \text{ mV} \sim 28.5 \text{ mV} (5\text{V})$ | |
| Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Accuracy | ±0.25% | |
| Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Voltage - Supply | 1.8 V ~ 12 V | |
| Features - Termination Style PC Pin Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Port Size | Male - 0.13" (3.18mm) Tube | |
| Termination Style PC Pin Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Port Style | Barbless | |
| Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Features | - | |
| Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Termination Style | PC Pin | |
| Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - | Maximum Pressure | 12.33 PSI (85 kPa) | |
| Supplier Device Package - | Operating Temperature | -40°C ~ 125°C | |
| | Package / Case | 4-DIP (0.453", 11.50mm), Top Port | |
| Report errors? | Supplier Device Package | - | |
| | | | Report errors? |

NBPDLNS060MGUNV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NBPDLNS060MGUNV Payment Methods



















NBPDLNS060MGUNV Shipping Methods













If you have any question about NBPDLNS060MGUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com