

NBPDLNS600MGUNV

NBPDLNS600MGUNV Information



For Reference Only

Part Number NBPDLNS600MGUNV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

DescriptionBRD MNT PRESSURE SENSORS**Package**4-DIP (0.453", 11.50mm), Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NBPDLNS600MGUNV Specifications

Manufacturer Part Number NBPDLNS600MGUNV Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Vented Gauge Operating Pressure 8.7 PSI (60 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 45 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -			
Category Sensors, Transducers Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Vented Gauge Operating Pressure 8.7 PSI (60 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 45 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Manufacturer Part Number	NBPDLNS600MGUNV	
Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Vented Gauge Operating Pressure Output Type Wheatstone Bridge Output 0 mV ~ 45 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature 4-0°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Sure Sure Sensors, Transducers NET Action of Top Port Name of Top	Manufacturer	Honeywell Sensing and Productivity Solutions	
Package4-DIP (0.453", 11.50mm), Top PortSeriesNBPPressure TypeVented GaugeOperating Pressure8.7 PSI (60 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 45 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure29.01 PSI (200 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package-	Category	Sensors, Transducers	
SeriesNBPPressure TypeVented GaugeOperating Pressure8.7 PSI (60 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 45 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure29.01 PSI (200 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package-		Pressure Sensors, Transducers	
Pressure Type Vented Gauge Operating Pressure 8.7 PSI (60 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 45 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package	Package	4-DIP (0.453", 11.50mm), Top Port	
Operating Pressure 8.7 PSI (60 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 45 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package	Series	NBP	
Output Type Wheatstone Bridge Output 0 mV ~ 45 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Pressure Type	Vented Gauge	
Output $0 \text{ mV} \sim 45 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size $Male - 0.13'' (3.18 \text{mm})$ Tube Port Style $Barbless$ Features $-$ Termination Style $PC Pin$ Maximum Pressure $29.01 PSI (200 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-DIP} (0.453'', 11.50 \text{mm})$, Top Port Supplier Device Package $-$	Operating Pressure	8.7 PSI (60 kPa)	
Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size $Male - 0.13" (3.18mm)$ Tube Port Style $Barbless$ Features $-$ Termination Style PC Pin Maximum Pressure $29.01 \text{ PSI } (200 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-DIP } (0.453", 11.50mm)$, Top Port Supplier Device Package	Output Type	Wheatstone Bridge	
Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package	Output	$0 \text{ mV} \sim 45 \text{ mV} (5\text{V})$	
Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Accuracy	$\pm 0.25\%$	
Port Style Barbless Features - Termination Style PC Pin Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Voltage - Supply	1.8 V ~ 12 V	
Features - Termination Style PC Pin Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Port Size	Male - 0.13" (3.18mm) Tube	
Termination Style PC Pin Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Port Style	Barbless	
$\begin{array}{lll} \mbox{Maximum Pressure} & 29.01 \mbox{ PSI } (200 \mbox{ kPa}) \\ \mbox{Operating Temperature} & -40^{\circ}\mbox{C} \sim 125^{\circ}\mbox{C} \\ \mbox{Package / Case} & 4-\mbox{DIP } (0.453", 11.50\mbox{mm}), \mbox{Top Port} \\ \mbox{Supplier Device Package} & - \end{array}$	Features	-	
Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Termination Style	PC Pin	
Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Maximum Pressure	29.01 PSI (200 kPa)	
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C	
	Package / Case	4-DIP (0.453", 11.50mm), Top Port	
Report errors?	Supplier Device Package	-	
		Report erro	rs?

NBPDLNS600MGUNV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NBPDLNS600MGUNV Payment Methods



















NBPDLNS600MGUNV Shipping Methods













If you have any question about NBPDLNS600MGUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com