

NBPDPNN030PGUNV

NBPDPNN030PGUNV Information



For Reference Only

Part Number NBPDPNN030PGUNV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRES 30PSI GAUG 12V DIP **Package** 4-DIP (0.453", 11.50mm), Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NBPDPNN030PGUNV Specifications

ManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPressure Sensors, TransducersPackage 4 -DIP $(0.453", 11.50mm)$, Top PortSeriesNBPPressure TypeVented GaugeOperating Pressure $30 \text{ PSI } (206.84 \text{ kPa})$ Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 105 \text{ mV } (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size-	N. C. D. W. I	AMB DD DAN 1000 D CAN THE
Category Sensors, Transducers Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Vented Gauge Operating Pressure 30 PSI (206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size - Port Style No Port Features - Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Manufacturer Part Number	NBPDPNN030PGUNV
Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Vented Gauge Operating Pressure 30 PSI (206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size - Port Style No Port Features - Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Manufacturer	Honeywell Sensing and Productivity Solutions
Package 4-DIP (0.453", 11.50mm), Top Port Series NBP Pressure Type Vented Gauge Operating Pressure 30 PSI (206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size - Port Style No Port Features - Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Category	Sensors, Transducers
SeriesNBPPressure TypeVented GaugeOperating Pressure30 PSI (206.84 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 105 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StylePC PinMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-DIP (0.453", 11.50mm), Top PortSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 30 PSI (206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size - Port Style No Port Features - Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Package	4-DIP (0.453", 11.50mm), Top Port
Operating Pressure Output Type Wheatstone Bridge Output OmV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size - Port Style No Port Features - Termination Style Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package - Output 30 PSI (206.84 kPa) 0 mV ~ 105 mV (5V) **Ending Ending	Series	NBP
Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 105 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size-Port StyleNo PortFeatures-Termination StylePC PinMaximum Pressure $60 \text{ PSI } (413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4-\text{DIP } (0.453'', 11.50 \text{mm}), \text{Top Port}$ Supplier Device Package-	Pressure Type	Vented Gauge
Output $0 \text{ mV} \sim 105 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size - Port Style No Port Features - Termination Style PC Pin Maximum Pressure $60 \text{ PSI } (413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4\text{-DIP } (0.453'', 11.50 \text{mm}), \text{ Top Port}$ Supplier Device Package -	Operating Pressure	30 PSI (206.84 kPa)
Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size - Port Style No Port Features - Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Output Type	Wheatstone Bridge
Voltage - Supply 1.8 V ~ 12 V Port Size - Port Style No Port Features - Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Output	$0 \text{ mV} \sim 105 \text{ mV} (5\text{V})$
Port Size - No Port Features - Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Accuracy	±0.25%
Port Style No Port Features - Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Voltage - Supply	1.8 V ~ 12 V
Features - Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Port Size	-
Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Port Style	No Port
Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Features	-
Operating Temperature -40°C ~ 125°C Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Termination Style	PC Pin
Package / Case 4-DIP (0.453", 11.50mm), Top Port Supplier Device Package -	Maximum Pressure	60 PSI (413.69 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	4-DIP (0.453", 11.50mm), Top Port
Report errors?	Supplier Device Package	-
		Report errors?

NBPDPNN030PGUNV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NBPDPNN030PGUNV Payment Methods



















NBPDPNN030PGUNV Shipping Methods













If you have any question about NBPDPNN030PGUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com