

NBPLANN030PGUNV

NBPLANN030PGUNV Information



For Reference Only

Part Number NBPLANN030PGUNV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR 30 PSIG UNAMPLIFIED SMD

Package 6-SMD, No Lead, Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NBPLANN030PGUNV Specifications

Manufacturer Part Number NBPLANN030PGUNV Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 6-SMD, No Lead, Top Port Series NBP Pressure Type Vented Gauge Operating Pressure 30 PSI (206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.11" (2.74mm) Tube Port Style Barbed Features - Termination Style Surface Mount Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -		
CategorySensors, TransducersPackage6-SMD, No Lead, Top PortSeriesNBPPressure TypeVented GaugeOperating Pressure30 PSI (206.84 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 105 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.11" (2.74mm) TubePort StyleBarbedFeatures-Termination StyleSurface MountMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-40°C ~ 125°CPackage / Case6-SMD, No Lead, Top PortSupplier Device Package-	Manufacturer Part Number	NBPLANN030PGUNV
Package 6-SMD, No Lead, Top Port Series NBP Pressure Type Vented Gauge Operating Pressure Output Type Wheatstone Bridge Output 0 mV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.11" (2.74mm) Tube Port Style Barbed Features - Termination Style Surface Mount Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Sure Port Sure Pressure 6-SMD, No Lead, Top Port Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions
Package6-SMD, No Lead, Top PortSeriesNBPPressure TypeVented GaugeOperating Pressure30 PSI (206.84 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 105 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.11" (2.74mm) TubePort StyleBarbedFeatures-Termination StyleSurface MountMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-40°C ~ 125°CPackage / Case6-SMD, No Lead, Top PortSupplier Device Package-	Category	Sensors, Transducers
SeriesNBPPressure TypeVented GaugeOperating Pressure30 PSI (206.84 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 105 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.11" (2.74mm) TubePort StyleBarbedFeatures-Termination StyleSurface MountMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-40°C ~ 125°CPackage / Case6-SMD, No Lead, Top PortSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 30 PSI (206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.11" (2.74mm) Tube Port Style Barbed Features - Termination Style Surface Mount Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Package	6-SMD, No Lead, Top Port
Operating Pressure 30 PSI (206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.11" (2.74mm) Tube Port Style Barbed Features - Termination Style Surface Mount Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Series	NBP
Output TypeWheatstone BridgeOutput0 mV ~ 105 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.11" (2.74mm) TubePort StyleBarbedFeatures-Termination StyleSurface MountMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-40°C ~ 125°CPackage / Case6-SMD, No Lead, Top PortSupplier Device Package-	Pressure Type	Vented Gauge
Output 0 mV ~ 105 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.11" (2.74mm) Tube Port Style Barbed Features - Termination Style Surface Mount Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Operating Pressure	30 PSI (206.84 kPa)
Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.11" (2.74mm) Tube Port Style Barbed Features - Termination Style Surface Mount Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Output Type	Wheatstone Bridge
Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.11" (2.74mm) Tube Port Style Barbed Features - Termination Style Surface Mount Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Output	$0 \text{ mV} \sim 105 \text{ mV} (5\text{V})$
Port Size Male - 0.11" (2.74mm) Tube Port Style Barbed Features - Termination Style Surface Mount Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Accuracy	±0.25%
Port Style Barbed Features - Termination Style Surface Mount Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Voltage - Supply	1.8 V ~ 12 V
Features - Termination Style Surface Mount Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Port Size	Male - 0.11" (2.74mm) Tube
Termination Style Surface Mount 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Port Style	Barbed
Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Features	-
Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Termination Style	Surface Mount
Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Maximum Pressure	60 PSI (413.69 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	6-SMD, No Lead, Top Port
Report errors?	Supplier Device Package	-
		Report errors?

NBPLANN030PGUNV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NBPLANN030PGUNV Payment Methods



















NBPLANN030PGUNV Shipping Methods













If you have any question about NBPLANN030PGUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com