

NBPLLNS060MGUNV

NBPLLNS060MGUNV Information



For Reference Only

Part Number NBPLLNS060MGUNV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description BRD MNT PRESSURE SENSORS

Package 6-SMD, No Lead, Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NBPLLNS060MGUNV Specifications

Manufacturer Part Number NBPLLNS060MGUNV Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 6-SMD, No Lead, Top Port Series NBP Pressure Type Vented Gauge Operating Pressure 0.87 PSI (6 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 28.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style Surface Mount Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package - Report errors?		
CategorySensors, TransducersPackage6-SMD, No Lead, Top PortSeriesNBPPressure TypeVented GaugeOperating Pressure0.87 PSI (6 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 28.5 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeatures-Termination StyleSurface MountMaximum Pressure12.33 PSI (85 kPa)Operating Temperature-40°C ~ 125°CPackage / Case6-SMD, No Lead, Top PortSupplier Device Package-	Manufacturer Part Number	NBPLLNS060MGUNV
Package 6-SMD, No Lead, Top Port Series NBP Pressure Type Vented Gauge Operating Pressure Output Type Wheatstone Bridge Output 4 0 mV ~ 28.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style Surface Mount Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Sure Port Sure Port Sup Port Sure Package / Case - SMD, No Lead, Top Port Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions
Package6-SMD, No Lead, Top PortSeriesNBPPressure TypeVented GaugeOperating Pressure0.87 PSI (6 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 28.5 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeatures-Termination StyleSurface MountMaximum Pressure12.33 PSI (85 kPa)Operating Temperature-40°C ~ 125°CPackage / Case6-SMD, No Lead, Top PortSupplier Device Package-	Category	Sensors, Transducers
SeriesNBPPressure TypeVented GaugeOperating Pressure0.87 PSI (6 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 28.5 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeatures-Termination StyleSurface MountMaximum Pressure12.33 PSI (85 kPa)Operating Temperature-40°C ~ 125°CPackage / Case6-SMD, No Lead, Top PortSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 0.87 PSI (6 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 28.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style Surface Mount Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package	Package	6-SMD, No Lead, Top Port
Operating Pressure Output Type Wheatstone Bridge Output OmV ~ 28.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case Supplier Device Package - 0.87 PSI (6 kPa) Wheatstone Bridge Wheatstone Bridge Wheatstone Bridge 40.87 No Lead, Top Port Supplier Device Package - Comparing Temperature -4.87 No Lead, Top Port	Series	NBP
Output TypeWheatstone BridgeOutput0 mV ~ 28.5 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeatures-Termination StyleSurface MountMaximum Pressure12.33 PSI (85 kPa)Operating Temperature-40°C ~ 125°CPackage / Case6-SMD, No Lead, Top PortSupplier Device Package-	Pressure Type	Vented Gauge
Output $0 \text{ mV} \sim 28.5 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size $\text{Male} - 0.13'' (3.18\text{mm}) \text{ Tube}$ Port Style Barbless Features $-$ Termination Style Surface Mount Maximum Pressure $12.33 \text{ PSI } (85 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case 6-SMD , No Lead, Top Port Supplier Device Package $-$	Operating Pressure	0.87 PSI (6 kPa)
Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style Surface Mount Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Output Type	Wheatstone Bridge
Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style Surface Mount Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Output	$0 \text{ mV} \sim 28.5 \text{ mV} (5\text{V})$
Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style Surface Mount Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Accuracy	±0.25%
Port Style Barbless Features - Termination Style Surface Mount Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Voltage - Supply	1.8 V ~ 12 V
Features - Termination Style Surface Mount Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Port Size	Male - 0.13" (3.18mm) Tube
Termination Style Surface Mount 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Port Style	Barbless
Maximum Pressure 12.33 PSI (85 kPa) Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Features	-
Operating Temperature -40°C ~ 125°C Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Termination Style	Surface Mount
Package / Case 6-SMD, No Lead, Top Port Supplier Device Package -	Maximum Pressure	12.33 PSI (85 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	6-SMD, No Lead, Top Port
Report errors?	Supplier Device Package	-
		Report errors?

NBPLLNS060MGUNV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NBPLLNS060MGUNV Payment Methods





















NBPLLNS060MGUNV Shipping Methods













If you have any question about NBPLLNS060MGUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com