

NBPMLNN015PAUNV

NBPMLNN015PAUNV Information



For Reference Only

Part Number NBPMLNN015PAUNV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR 15 PSIA UNAMPLIFIED SMD

Package 4-SMD, J-Lead, Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NBPMLNN015PAUNV Specifications

Manufacturer Part Number NBPMLNN015PAUNV Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 4-SMD, J-Lead, Top Port Series NBP Pressure Type Absolute Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 75 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style Surface Mount Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -		
CategorySensors, TransducersPackage4-SMD, J-Lead, Top PortSeriesNBPPressure TypeAbsoluteOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 75 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeatures-Termination StyleSurface MountMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SMD, J-Lead, Top PortSupplier Device Package-	Manufacturer Part Number	NBPMLNN015PAUNV
Package 4-SMD, J-Lead, Top Port Series NBP Pressure Type Absolute Operating Pressure Output Type Wheatstone Bridge Output 0 mV ~ 75 mV (5V) Accuracy ±0.25% Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style Surface Mount Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions
Package4-SMD, J-Lead, Top PortSeriesNBPPressure TypeAbsoluteOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 75 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeatures-Termination StyleSurface MountMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SMD, J-Lead, Top PortSupplier Device Package-	Category	Sensors, Transducers
SeriesNBPPressure TypeAbsoluteOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 75 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeatures-Termination StyleSurface MountMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SMD, J-Lead, Top PortSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeAbsoluteOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 75 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeatures-Termination StyleSurface MountMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SMD, J-Lead, Top PortSupplier Device Package-	Package	4-SMD, J-Lead, Top Port
Operating Pressure Output Type Wheatstone Bridge Output OmV ~ 75 mV (5V) Accuracy ±0.25% Voltage - Supply Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case Supplier Device Package - 15 PSI (103.42 kPa) Wheatstone Bridge Wheatstone Bridge Wheatstone Bridge And No	Series	NBP
Output TypeWheatstone BridgeOutput0 mV ~ 75 mV (5V)Accuracy±0.25%Voltage - Supply1.8 V ~ 12 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarblessFeatures-Termination StyleSurface MountMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SMD, J-Lead, Top PortSupplier Device Package-	Pressure Type	Absolute
Output $0 \text{ mV} \sim 75 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port Size $Male - 0.13'' (3.18 \text{mm})$ Tube Port Style $Barbless$ Features $-$ Termination Style $Surface Mount$ Maximum Pressure $30 \text{ PSI} (206.84 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4-\text{SMD}$, J-Lead, Top Port Supplier Device Package $-$	Operating Pressure	15 PSI (103.42 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $1.8 \text{ V} \sim 12 \text{ V}$ Port SizeMale - $0.13''$ (3.18mm) TubePort StyleBarblessFeatures-Termination StyleSurface MountMaximum Pressure $30 \text{ PSI } (206.84 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case 4-SMD , J-Lead, Top PortSupplier Device Package-	Output Type	Wheatstone Bridge
Voltage - Supply 1.8 V ~ 12 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style Surface Mount Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Output	0 mV ~ 75 mV (5V)
Port Size Male - 0.13" (3.18mm) Tube Port Style Barbless Features - Termination Style Surface Mount Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Accuracy	±0.25%
Port Style Barbless Features - Termination Style Surface Mount Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Voltage - Supply	1.8 V ~ 12 V
Features - Termination Style Surface Mount Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Port Size	Male - 0.13" (3.18mm) Tube
Termination Style Surface Mount 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Port Style	Barbless
Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Features	-
Operating Temperature -40°C ~ 125°C Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Termination Style	Surface Mount
Package / Case 4-SMD, J-Lead, Top Port Supplier Device Package -	Maximum Pressure	30 PSI (206.84 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	4-SMD, J-Lead, Top Port
Report errors?	Supplier Device Package	-
		Report errors?

NBPMLNN015PAUNV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NBPMLNN015PAUNV Payment Methods



















NBPMLNN015PAUNV Shipping Methods













If you have any question about NBPMLNN015PAUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com